

ESD soldering gun with solder feed 50 W for CA stations - JBC AP250-B

Item no. WL32736

Manufacturer JBC

The AP250-A is an ESD soldering gun with integrated solder feed for the modular JBC CA solder feed stations. It delivers 50 W at 24 V and ships with the C250403 tip and the SN5450 tin coil. Ideal when wire and iron need to be handled in one hand.

TECHNICAL DATA

Ausführungsklasse	ESD (antistatic)
Weight	0.1 kg



STANDARDS & COMPLIANCE

ESD safe IEC 61340-5-1

DESCRIPTION

The AP250-A feeds solder wire right at the handpiece, so you can run repetitive joints one handed. Rated 50 W at 24 V, it works on the modular JBC CA stations and comes fitted with the C250403 tip and the SN5450 tin coil.

BENEFITS

- Integrated solder feed for one handed soldering of production joints
- 50 W at 24 V for fast heat recovery at the joint
- Uses C250 series tips, supplied with C250403 (1 mm)
- Handles solder wire from 0.06 to 1.5 mm diameter
- ESD safe build for use at protected workstations

TECHNICAL DATA

Item no.	WL32736
Model	AP250-A
Manufacturer	JBC

Manufacturer item no.	AP250-A
Dimensions with packaging (LxWxH)	245 mm x 185 mm x 45 mm
Nominal power	50 W
Voltage	24 V
Handle type	soldering gun
With soldering tip	yes
Included soldering tip	C250403
Suitable tips	C250
Soldering tip shape	other
Soldering tip diameter	1 mm
Wire diameter	0.06-1.5 mm
Compatible soldering stations	CA
Suitable control unit	DI, DDE, DME
Suitable accessories	F1204 Fume extractor
Order unit	piece

APPLICATIONS

Production soldering, rework and repair where solder wire has to be fed in a controlled, one handed manner.

COMPATIBILITY AND SCOPE OF DELIVERY

Suitable for the modular CA solder feed stations and the DI, DDE and DME control units. The F1204 fume extractor is available as an accessory. The scope of delivery includes the soldering gun, the C250403 tip and the SN5450 tin coil.

ESD safe for workplaces in accordance with IEC 61340-5-1. Made in Spain.