

C.K T3886. Ecotronic ESD side cutters, head flattened, slim design, 139 mm

Item no. WL33748

Manufacturer C.K

Ecotronic ESD side cutters, head flattened, slim design, 139 mm

TECHNICAL DATA

Ausführungsklasse **ESD (antistatic)**Weight **0.1 kg**

STANDARDS & COMPLIANCE

ESD safe

DESCRIPTION

- Light Precision
- Side cutters for finest cutting applications (e.g. micro electronics and precision engineering)
- Suitable for cutting soft copper wires up to 1.3 mm Ø / 16AWG
- Slim cutting head, conical shape, flattened, for better access in very narrow, narrow spaces
- Sharp cutting edges with precision grinding for flush cutting
- Blade of special tool steel, hardened for long cutting performance
- Electrostatic dissipative handles - dissipative resistor 10⁸
- Two-component handles in convex design for comfortable working
- Black burnished surface for corrosion protection and reduced glare
- Smooth-running return spring for improved comfort during repetitive work
- Joint with sturdy stainless steel rivet
- Technical information:
 - total length: 139 mm
 - Blade length: 10 mm
 - Cutting angle: 21
 - head height (from trade to tip): 21 mm

- Head width (widest point): 11 mm
- steel thickness: 2,5 mm
- Cutting capacity (copper only) : 1.3 mm / 16 AWG

PRODUCT DETAILS

item number	WL33748
model	T3886
manufacturer	C.K
manufacturer item number	T3886
dimensions (LxWxH)	0 x 139 mm x 70 mm
dimensions with packaging (LxWxH)	2.5 mm x 220 mm x 80 mm
order unit	piece
VDE	no
ESD safe	yes
tool length	139 mm
type of side cutter	side cutter