

ESD tape dispenser made of ABS, 210 x 110 x 77 mm, dissipative - Safeguard WL33941

Item no. WL33941

Manufacturer Safeguard

Dissipative ESD tape dispenser made of ABS for tapes up to 25 mm wide and a 76 mm core. Thanks to its carbon additive and ESD marking it is safe to use inside the ESD protected area.

TECHNICAL DATA

Ausführungsklasse	ESD (antistatic)
Depth	210
Height	77
Norm	IEC 61340-5-1
Sales unit	1 Stück
Weight	0.1 kg
Width	110



STANDARDS & COMPLIANCE

ESD safe IEC 61340-5-1

DESCRIPTION

The Safeguard ESD tape dispenser keeps tape rolls within reach at the ESD workstation without causing a static charge. The carbon-loaded ABS housing is permanently dissipative, carries an ESD marking and is approved for use inside the EPA.

BENEFITS

- Carbon-loaded ABS housing, permanently dissipative
- ESD marking
- For tapes up to 25 mm wide and a 76 mm core

TECHNICAL DATA

- Material: ABS
- Dimensions: 210 x 110 x 77 mm (L x W x H)
- Max. tape width: 25 mm
- Core: 76 mm dia.
- Typical dissipation resistance: $R_{gp} < 10^8 \text{ Ohm}$
- Selling unit: 1 piece

APPLICATION

Providing tape at packing and assembly workstations within the ESD protected area.

STANDARDS AND COMPLIANCE

Suitable for use according to IEC 61340-5-1.