

Kapton/polyimide tape UL510 8 mm x 33 m, dissipative, up to 300 C

Item no. WL34002

Manufacturer A1-ESD

Dissipative polyimide solder masking tape (Kapton) to UL510, 8 mm wide, 33 m. Short-term resistant up to 300 C and residue-free removable.

TECHNICAL DATA

Ausführungsklasse	ESD (antistatic)
Country of Manufacture	Germany
HS-Code	85159080900
Norm	UL 510
Weight	0.1 kg



DESCRIPTION

Dissipative Kapton/polyimide tape to UL510, 8 mm wide and 33 m long. The amber tape protects contact surfaces in the solder wave, removes without residue and is chemical resistant. Made in EU.

BENEFITS

- Short-term heat resistant up to 300 C
- Dissipative material, flame retardant to UL510
- Residue-free removable and chemical resistant
- Core diameter 76 mm, amber colour

TECHNICAL DATA

Item number	WL34002
Model	885608
Material	Polyimide, dissipative
Width	8 mm
Length	33 m
Core diameter	76 mm
Film thickness	0.06 mm

Standard	UL510
Origin	Made in EU
Sales unit	1 roll

APPLICATIONS

Masking of contact surfaces in the solder wave and during selective and wave soldering.