

cab 8916702. ESD PCB magazine 702.2, polycarbonate, 320x400x563 mm

Item no. WL34830**Manufacturer cab**

ESD PCB magazine 702.2, polycarbonate, 320x400x563 mm

TECHNICAL DATA

Ausführungsklasse **ESD (antistatic)**Weight **0.1 kg**

STANDARDS & COMPLIANCE

ESD safe

DESCRIPTION

PCB magazines series 700: Variable width adjustment by toothed belt by hand

Safety screw

Clamping of the toothed belt by a knurled screw prevents accidental adjustment of the movable side wall.

Four precision spindles

for adjusting the movable side wall

Transport lock

A latch is mounted on the front and rear as standard. When lifted, the latch is moved outwards and locks in the upper position. The PCBs can be inserted or removed. When lifted again, the guides are locked.

Toothed belt

By pulling the toothed belt, the web walls are adjusted to the required PCB width.

- Model: 702.2
- Slot depth 3 mm
- partially assembled, with transport lock

- LP: W = 40-250 mm (adjustable), L max = 787 mm
- Magazine: H x W x D = 400 x 320 x 563 mm
- Plastic web wall
- width adjustment by toothed belt
- stackable (with stacking knobs) or for turning operation

PRODUCT DETAILS

item number	WL34830
model	8916702
manufacturer	CAB
manufacturer item number	8916702
order unit	piece
temperature max.	130 °C
ESD safe	yes
Series PCB magazines	Series 700
Material PCB magazine	plastic