

3-channel rework station WXR 3030, 600 W, soldering desoldering hot air - Weller WXR 3030

Item no. WL34966

Manufacturer Weller

Multifunctional 3-channel rework station with 600 W total power and intelligent power management for soldering, desoldering and hot air. Two integrated pumps make it independent of external compressed air.

TECHNICAL DATA

Ausführungsklasse **ESD (antistatic)**

Country of Manufacture **Germany**

HS-Code **85151990000**

Weight **0.1 kg**


STANDARDS & COMPLIANCE

ESD safe IEC 61340-5-1

DESCRIPTION

The WXR 3030 is a multifunctional 3-channel rework station combining soldering, desoldering and hot air in one system. With 600 W total power (3 channels of 200 W each) and intelligent power management it distributes the available power to the connected WX tools as required, so high-performance tools can run simultaneously.

BENEFITS

- 600 W total power across 3 channels for demanding rework
- Intelligent power management distributes power on demand
- Two integrated pumps, independent of external compressed air
- Integrates into traceability processes, USB interface for firmware, parameterization and monitoring
- Backlit LCD (240 x 88 px) shows all connected tools
- IPC compliant, WX compatible

TECHNICAL DATA

Model

WXR 3030

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Model line	WXR 3
Manufacturer item no.	T0053501699N
Total power	600 W (3 x 200 W)
Number of channels	3
Temperature range	100-450°C / 200-850°F
Temperature stability	±2°C
Vacuum	max. 0.7 bar
Max. hot air volume	15 l/min (tool dependent)
Flow rate	18 l/min
Display	240 x 88 px, backlit
Overcurrent release	2.0 A
Dimensions (LxWxH)	273 x 235 x 102 mm

APPLICATIONS

Complete rework on populated PCBs in manufacturing, repair and lab: soldering, desoldering and hot air at one workstation.

SCOPE OF SUPPLY & COMPATIBILITY

Supplied with: WXR 3 supply unit (420 W), WXHAP 200 hot air iron set, WXDP 120 desoldering iron set (horizontal), WXP 65 soldering iron set, WVP vacuum pipette and PDN desoldering nozzle pliers. All WX tools can be connected.

ESD-safe and IPC compliant to IEC 61340-5-1. Origin: Germany.