

Waldmann
113053000-00580588.
Surface mounted light MACH
LED Plus.seventy - MQAL 18
S, L: 510 mm, Eco

Item no. WL35498

Manufacturer Waldmann

Surface mounted light MACH LED PLUS.seventy - MQAL 18 S, L:
510 mm, Eco

TECHNICAL DATA

Weight

0.1 kg**DESCRIPTION**

Maintenance-free LED technology. Eco version. Very low-glare, homogeneous light with soft transitions. Outer diameter 70 mm for the replacement of classic tubular lights. Robust aluminium housing with solid safety glass cover. Side parts made of high performance plastic. Sealed M12 connector. Viton seal for a high degree of protection. Chemically resistant to many media such as oils or cooling lubricants. Insensitive to shocks and vibrations. Ideal for high mechanical and thermal loads. Connection to machine voltage.

- without control gear
- Connected loads: 18-30 V; DC
- Luminous flux: approx. 750 lm
- luminous efficacy: approx. 93 lm/W
- Light distribution: direct
- Light colour: neutral white
- Colour rendering (Ra): > 80
- Technology: switchable
- Operation: external
- Lamp cover: Lens shade, clear (colourless)
- Mains connection: 763 series connectors
- Type: Surface-mounted version
- Mounting: L-angle (accessory), clamp (accessory)

- Length: 510 mm
- Special feature: Eco-assembly
- Em: 273 lx, Emax: 354 lx, Emin: 169 lx (measuring distance 100 cm)

PRODUCT DETAILS

item number	WL35498
model	MQAL 18 S
manufacturer	WALDMANN
manufacturer item number	113053000-00580588
length	845 mm
width	90 mm
depth	80 mm
order unit	piece
luminous flux	750 lm
Lamp or magnifier type	Surface mounted light
connections	18-30 V; DC
colour temperature	5000 °K
power	7.5 W
equipping	LED, energy efficiency class A+
housing colour	Aluminium, anodised, aluminium coloured (colourless anodised)
protection class	3
protection class	67 IP
ESD safe	no