

Desoldering nozzle 21.0 x 13.3 mm for 48-pin TSOP, HCT-900 - Oki H-TS48

Item no. WL36524

Manufacturer Oki

A 48-pin TSOP comes off cleanly only when the hot air reaches both lead rows at the same time. The H-TS48 nozzle measures 21.0 mm x 13.3 mm and encloses the package precisely. Accessory for the HCT-900 hand-held convection tool.

TECHNICAL DATA

Weight

0.1 kg



DESCRIPTION

On a 48-pin TSOP the fine leads sit closely spaced along two long package sides. If the hot air does not reach them simultaneously, pins bend or neighbouring parts lift with the target. The Oki H-TS48, sized 21.0 mm x 13.3 mm, guides the air onto the package with a matched opening.

BENEFITS

- Inner size 21.0 mm x 13.3 mm matched to 48-pin TSOP packages
- Enclosing air guidance for even reflow of all leads
- Confined heat input protects neighbouring parts on densely populated boards
- Single nozzle for targeted extension of an existing nozzle set

TECHNICAL DATA

Item number	WL36524
Model	H-TS48
Manufacturer	OKI
Manufacturer item number	H-TS48
Dimensions	21.0 mm x 13.3 mm
Package type	TSOP, 48 pin
Matching system	HCT-900

APPLICATIONS

Removing and placing 48-pin TSOP components such as memory devices in repair, rework, failure analysis and sample building.

COMPATIBILITY AND SCOPE OF DELIVERY

For the Oki HCT-900 hand-held convection tool. Delivery comprises one desoldering nozzle. It is also part of the NZKT-1 nozzle set.