

Knipex 79 42 125 Z. Precision electronics side cutter, for soft materials, 125 mm

Item no. WL37383

Manufacturer Knipex

Precision electronics side cutter, for soft materials, 125 mm

TECHNICAL DATA

Weight

0.1 kg



STANDARDS & COMPLIANCE

ISO 9654

DESCRIPTION

Precision pliers for the finest cutting work, e.g. in electronics and precision mechanics. Very precisely ground, sharp cutting edges with very small facets for exact cuts on sensitive electronic components; also available without facet for flush cutting. Cutting edges additionally induction hardened, cutting edge hardness approx. 64 HRC. Approx. 20 % less weight than conventional electronic pliers. Bolted joint with particularly carefully manufactured joint surfaces for uniform, low-friction movement in the entire opening range. Smooth-running double spring for smooth and even opening. Ergonomically optimised multi-component sheaths. for an optimised flush cutting result on soft materials. for assemblies with tight tolerances, for precise wire end configuration. - cutting values soft wire (diameter): Ø 0,1 - 1,3mm - jaw length (B): 11mm - jaw thickness (at joint) (D): 6,5mm - head width (A): 11mm

- Precision pliers for finest cutting work, e.g. in electronics and precision mechanics
- Very precisely ground, sharp cutting edges with very small facets for exact cuts on sensitive electronic components
- Also without facet for flush cutting
- Cutting edges additionally induction hardened, cutting edge hardness approx. 64 HRC

- Approx. 20 % less weight than conventional electronic pliers
- Bolted joint with particularly carefully manufactured joint surfaces for uniform, low-friction movement in the entire opening range
- Smooth-running double spring for smooth and even opening
- Ergonomically optimised multi-component sleeves

PRODUCT DETAILS

item number	WL37383
model	79 42 125 Z
manufacturer	KNIPEX
manufacturer item number	79 42 125 Z
dimensions (LxWxH)	120 mm x 60 mm x 19 mm
dimensions with packaging (LxWxH)	189 mm x 72 mm x 48 mm
Packaging volume	0.637 dm ³
order unit	piece
type of packaging	single pack
standards	DIN ISO 9654
RoHS conform	no
surface	burnished
VDE	no
ESD safe	no
tool length	125 mm
type of side cutter	side cutter
type of handle	with multi-component sleeves
cutting value wire diameter soft	1.3 mm