

Thermaltronics TMT-5000S-2. Soldering station TMT-5000S-2, w/SHP-T 220-240VAC

Item no. WL37531

Manufacturer Thermaltronics

Soldering station TMT-5000S-2, w/SHP-T 220-240VAC

TECHNICAL DATA

Power	30 W
Temperature (max.)	bis 500 °C
Temperature range	325-475 °C
Weight	0.1 kg



DESCRIPTION

- Idle temperature stability: +/- 1.1 °C (2 °F)
- Maximum enclosure temperature: 50 °C (122 °F)
- Surface resistance: 105 - 109 Ω/sq
- Voltage soldering tip to ground: <2 mV
- No training required for calibration and use
- No additional costs for coil mounting
- Curie thermal technology - operation at 13.56 MHz
- Mains voltage: TMT-5000PS-2 220-240 VAC, 52W
- Resistance Soldering tip to ground: <2 Ohms DC
- Fuse: TMT-5000PS-2 250V 0.5A "Slo-Blo"
- Max. Power output: 30 Watt
- Output frequency: 13.56 MHz
- compact, takes up very little working space

PRODUCT DETAILS

item number	WL37531
model	TMT-5000S-2
manufacturer	THERMALTRONICS
manufacturer item number	TMT-5000S-2

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

dimensions (LxWxH)	117 mm x 112 mm x 205 mm
dimensions with packaging (LxWxH)	380 mm x 240 mm x 190 mm
dimensions with packaging in inches (LxWxH)	15 in x 9.4 in x 7.5 in
scope of supply	TMT-5000PS power supply unit SHH-2 Soldering Iron Tray SHP-T Soldering handpiece RMP-1 Protective cloth for tip removal SG-1-GR Soldering handpiece, green handle SG-1-BK Soldering handpiece, black handle BC-1 Brass braiding SPG-1 Sulfide-free sponge CC-1 Connection cable
order unit	piece
frequency	50/60 Hz
suitable tips	T series
station type	soldering station
included accessories	RMP-1 Protection cloth for tip removal, SG-1-GR soldering handpiece green handle, SG-1-BK soldering handpiece, black handle, BC-1 brass braid, SPG-1 sulfide-free sponge, CC-1 connection cable
included stand	SHH-2
included control unit	TMT-5000PS
included handpiece	SHP-T