

Bevelled soldering tip 60° 1 mm, bevelled face only tinned - Thermaltronics K60BVF010

Item no. WL37552

Manufacturer Thermaltronics

Replaceable K-series soldering tip, bevelled 60°, 1 mm tip width, for the SHP-K and SHP-KM handpieces. Working temperature 325 to 358 °C, RoHS compliant and lead-free.

TECHNICAL DATA

Ausführungsklasse **ESD (antistatic)**

Country of Manufacture **United States**

HS-Code **85159080900**

Weight **0.1 kg**


DESCRIPTION

The Thermaltronics K-series bevelled soldering tip 60° 1 mm transfers heat to the joint through Curie point technology and holds the temperature in the 325 to 358 °C range without external sensors. On this model only the bevelled face is tinned, which supports precise soldering on densely populated boards.

BENEFITS

- 1 mm tip width for fine soldering work
- Self-regulating temperature 325 to 358 °C, no calibration needed
- Tool-free change on the SHP-K and SHP-KM handpieces
- RoHS compliant and lead-free

TECHNICAL DATA

Manufacturer article no.	K60BVF010
Tip series	K series / Series 600
Tip shape	bevelled 60°
Tip width	1 mm (0.04 in)
Tip length	15 mm
Temperature range	325 to 358 °C

Suitable handpiece

SHP-K, SHP-KM

RoHS / lead-free

yes

APPLICATIONS

PCB assembly and rework, through-hole and surface-mount joints, and general electronics repair.

COMPATIBILITY

Fits the TMT-2000S-K soldering station and the TMT-2000PS power supply with the SHP-K or SHP-KM handpiece, as well as OKI PS-900 and MFR-PS1100/MFR-PS2200 with SHP-KM. Supplied as a single tip (1 piece).