

Bevelled soldering tip 45° 6.0 mm, only bevelled face tinned - Thermaltronics K60BVF060

Item no. WL37556

Manufacturer Thermaltronics

Lead-free K series soldering tip (bevelled) with 6.0 mm tip width for fine to medium work on SMD and through-hole assemblies. Fits the SHP-K and SHP-KM handpieces, 325 to 358 °C working range, RoHS compliant.

TECHNICAL DATA

Ausführungsklasse **ESD (antistatic)**

Country of Manufacture **United States**

HS-Code **85159080900**

Temperature range **325-358 °C**

Weight **0.1 kg**


STANDARDS & COMPLIANCE

ESD safe

DESCRIPTION

The bevelled K60BVF060 soldering tip from the Thermaltronics K series delivers heat to the joint through the inductive Smart Heat process and holds the working temperature in the 325 to 358 °C range without calibration.

BENEFITS

- Bevelled geometry tinned only on the angled face for drag soldering and larger pads
- Tip width 6.0 mm for targeted heat delivery matched to component size
- Lead-free and RoHS compliant, suited to modern lead-free alloys
- Direct swap on the SHP-K and SHP-KM handpieces

TECHNICAL DATA

Manufacturer part no.	K60BVF060
Item no.	WL37556
Product series	K soldering tip series, Series 600
Tip shape	bevelled 45°

Tip width	6.0 mm (0.24 in)
Tip length	15 mm (0.59 in)
Temperature range	325 to 358 °C
Type	soldering tip
Compatible handpiece	SHP-K, SHP-KM
Compliance	RoHS, lead-free

APPLICATIONS

SMD and through-hole soldering in electronics manufacturing, repair and the lab, from fine component work to larger pads.

COMPATIBILITY

Fits the SHP-K and SHP-KM handpieces and the TMT-2000S-K, TMT-2000PS and PS900 stations, and through SHP-KM the Oki MFR-PS1100 and MFR-PS2200.

ESD safe, RoHS compliant, lead-free. Made in the USA.