

Chisel soldering tip 30° 1.0 mm - Thermaltronics K60CH010

Item no. WL37563

Manufacturer Thermaltronics

Lead-free K series soldering tip (chisel) with 1.0 mm tip width for fine to medium work on SMD and through-hole assemblies. Fits the SHP-K and SHP-KM handpieces, 325 to 358 °C working range, RoHS compliant.

TECHNICAL DATA

Ausführungsklasse	ESD (antistatic)
Country of Manufacture	United States
HS-Code	85159080900
Temperature range	325-358 °C
Weight	0.1 kg



STANDARDS & COMPLIANCE

ESD safe

DESCRIPTION

The chisel K60CH010 soldering tip from the Thermaltronics K series delivers heat to the joint through the inductive Smart Heat process and holds the working temperature in the 325 to 358 °C range without calibration.

BENEFITS

- Chisel 30° geometry with good heat transfer for in-line and connector soldering
- Tip width 1.0 mm for targeted heat delivery matched to component size
- Lead-free and RoHS compliant, suited to modern lead-free alloys
- Direct swap on the SHP-K and SHP-KM handpieces

TECHNICAL DATA

Manufacturer part no.	K60CH010
Item no.	WL37563
Product series	K soldering tip series, Series 600
Tip shape	chisel

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Tip width	1.0 mm (0.04 in)
Tip length	11.4 mm (0.45 in)
Temperature range	325 to 358 °C
Type	soldering tip
Compatible handpiece	SHP-K, SHP-KM
Compliance	RoHS, lead-free

APPLICATIONS

SMD and through-hole soldering in electronics manufacturing, repair and the lab, from fine component work to larger pads.

COMPATIBILITY

Fits the SHP-K and SHP-KM handpieces and the TMT-2000S-K, TMT-2000PS and PS900 stations, and through SHP-KM the Oki MFR-PS1100 and MFR-PS2200.

ESD safe, RoHS compliant, lead-free. Made in the USA.