

Lötspitze Hufform mit Dent 60°, 3,1 mm, 325-358 °C, Serie K - Thermaltronics K60WV031

Item no. **WL37603**

Manufacturer **Thermaltronics**

Hoof-shaped Series K soldering tip with dent, 60° and 3.1 mm tip width for the SHP-K and SHP-KM handpieces. Working range 325-358 °C, well suited to drag soldering and removing solder bridges. RoHS compliant and lead-free.

TECHNICAL DATA

Ausführungsklasse **ESD (antistatic)**

Country of Manufacture **United States**

HS-Code **85159080900**

Temperature range **325-358 °C**

Weight **0.1 kg**



DESCRIPTION

The K60WV031 hoof-shaped soldering tip with dent holds more solder at the tip thanks to its recess and suits drag soldering, removing bridges and reflowing joints. The 3.1 mm wide tip works in the 325-358 °C range.

KEY BENEFITS

- Hoof shape with dent for greater solder load and clean drag soldering
- 60° angle and 3.1 mm width for fine to medium joints
- Temperature range 325-358 °C for lead-free joints
- RoHS compliant and lead-free

TECHNICAL DATA

Item no.	WL37603
Manufacturer no.	K60WV031
Series	K soldering tip series / Series 600
Temperature range	325-358 °C
Tip shape	hoof with dent, 60°
Tip width	3.1 mm (0.12 in)
Tip length	16.4 mm (0.65 in)

Order unit

piece

APPLICATIONS

Drag soldering, removing solder bridges, rework on SMD and THT joints.

COMPATIBILITY AND SCOPE OF SUPPLY

Fits the SHP-K and SHP-KM handpieces, used with TMT-2000S-K, TMT-2000PS, PS900 and MFR-PS1100/MFR-PS2200. Supplied as a single piece.

RoHS compliant, lead-free.