

Bevelled soldering tip 60° 1 mm (0.04"), lead-free - Thermaltronics M6BV010

Item no. WL37749

Manufacturer Thermaltronics

Lead-free M-series soldering tip 1 mm, bevelled 60°, for Thermaltronics TMT-9000S stations and Metcal MX-500/MX-5000/MX-5200 with the SHP-1 handpiece. Working range 325-358 °C, RoHS compliant.

TECHNICAL DATA

Ausführungsklasse	ESD (antistatic)
Country of Manufacture	United States
HS-Code	85159080900
Weight	0.1 kg



DESCRIPTION

The Bevelled soldering tip 60° 1 mm (0.04"), lead-free is a lead-free M-series replacement soldering tip with a 1 mm wide, 60° bevelled face. It delivers heat from the Thermaltronics SmartHeat technology straight to the joint and holds the 325-358 °C working range without calibration.

KEY BENEFITS

- Bevelled face 1 mm / 0.04" for drag soldering and multi-pin parts
- Self-regulating M-series working range 325-358 °C
- RoHS compliant and lead-free

TECHNICAL DATA

Item no.	WL37749
Manufacturer item no.	M6BV010
Series	M soldering tip series
Tip type	Soldering tip
Tip alignment	bevelled
Bevel angle	60°
Tip width	1 mm (0.04")

Tip length	13.4 mm (0,53 in)
Temperature range	325-358 °C
Suitable handpiece	SHP-1
Packaging size (LxWxH)	174 mm x 35 mm x 12 mm

APPLICATIONS

Suited to lead-free hand and rework soldering of through-hole and SMD components in electronics manufacturing, repair and laboratory work.

COMPATIBILITY AND SCOPE OF DELIVERY

Fits the Thermaltronics TMT-9000S-1 and TMT-9000S-2 soldering stations and the Metcal MX-500, MX-5000 and MX-5200 used with the SHP-1 handpiece. Scope of delivery: 1 soldering tip.

RoHS compliant, lead-free. Country of origin: USA.