

Soldering tip hook-shaped long 30° Fine 0,51mm (0,02") for SHP-1, 420 to 475 °C - Thermaltronics M8MD575

Item no. WL37996

Manufacturer Thermaltronics

Replaceable M-series soldering tip hook-shaped long 30° Fine 0,51mm (0,02") for the SHP-1 handpiece, tip width 0,51 mm (0,02 in). Operating temperature 420 to 475 °C, RoHS compliant and lead-free. Fits TMT-9000S and Metcal MX-500, MX-5000 and MX-5200.

TECHNICAL DATA

Ausführungsklasse	ESD (antistatic)
Country of Manufacture	United States
HS-Code	85159080900
Weight	0.1 kg



STANDARDS & COMPLIANCE

ESD safe

DESCRIPTION

The M8MD575 soldering tip replaces worn M-series tips on the SHP-1 handpiece without reconfiguring the soldering unit. With a tip width of 0,51 mm (0,02 in) and a hook-shaped long 30° Fine 0,51mm (0,02") geometry it suits targeted lead-free soldering across the 420 to 475 °C range.

BENEFITS

- Tip width 0,51 mm (0,02 in) for the right thermal coupling to the joint
- Operating temperature 420 to 475 °C of the M soldering tip series
- RoHS compliant and lead-free
- Changed on the SHP-1 handpiece without tools
- Replaces Metcal article no. SMTC-8172

TECHNICAL DATA

Article no.	WL37996
Model / manufacturer no.	M8MD575
Manufacturer	Thermaltronics

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

Product series	M soldering tip series
Temperature range	420 to 475 °C
Tip width	0,51 mm (0,02 in)
Tip length	15,4 mm (0,61 in)
Compatible handpiece	SHP-1
Order unit	piece
Replaces Metcal	article no. SMTC-8172

APPLICATIONS

Lead-free hand and rework soldering of electronic assemblies, repair and rework on printed circuit boards.

COMPATIBILITY & SCOPE OF DELIVERY

- Compatible handpiece: SHP-1
- Suitable for: TMT-9000S-1, TMT-9000S-2, MX-500, MX-5000, MX-5200
- Scope of delivery: 1 soldering tip M8MD575

RoHS compliant, lead-free, ESD-safe in use. Manufacturer: Thermaltronics (USA).