

Soldering tip chisel 90° 3mm (0.12 in), P series - Thermaltronics PM60CH181

Item no. WL38059

Manufacturer Thermaltronics

P series soldering tip for the Thermaltronics PM60CH181, chisel shape, 3mm (0.12 in) width, 5.2 mm (0.2 in) length. Operating temperature 325-358 °C, lead-free and RoHS compliant. Fits the SHP-P, SHP-PM handpieces.

TECHNICAL DATA

Ausführungsklasse	ESD (antistatic)
Country of Manufacture	United States
HS-Code	85159080900
Weight	0.1 kg



STANDARDS & COMPLIANCE

ESD safe

DESCRIPTION

This P series soldering tip delivers heat precisely to the joint on Thermaltronics Curie-point heating systems. With a tip width of 3mm (0.12 in) and a chisel shape, it supports repeatable soldering within the fixed temperature window 325-358 °C.

BENEFITS

- Chisel shape, 3mm (0.12 in) width, 5.2 mm (0.2 in) length
- Fixed P series temperature window 325-358 °C for consistent results
- Lead-free and RoHS compliant

TECHNICAL DATA

Item no.	WL38059
Manufacturer item no.	PM60CH181
Manufacturer	Thermaltronics
Product series	P soldering tip series, 325-358 °C
Type	Soldering tip

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

Tip shape	chisel
Tip width	3mm (0.12 in)
Tip length	5.2 mm (0.2 in)
Temperature range	325-358 °C
Suitable handpiece	SHP-P, SHP-PM

APPLICATIONS

Suitable for lead-free and conventional soldering in electronics manufacturing, repair and rework, from fine to medium joints depending on tip width.

COMPATIBILITY AND SCOPE OF SUPPLY

Fits the SHP-P, SHP-PM soldering handpieces and works on the following systems: TMT-2000PS, MFR-PS1100, MFR-PS2200, MFR-PS1K, MFR-PS2K. Supplied as a single tip (1 piece).

Lead-free, RoHS compliant, suitable for ESD-safe work on a grounded Thermaltronics system.