

Soldering tip micro fine 0,25 mm (0,01 in), 325-358 °C - Thermaltronics PM60MF375

Item no. WL38083

Manufacturer Thermaltronics

Lead-free P-series micro fine tip with 0,25 mm tip width for the 325 to 358 °C working range. Fits the SHP-P, SHP-PM handpieces of the Thermaltronics TMT-2000 and Oki MFR-PS systems.

TECHNICAL DATA

Ausführungsklasse	ESD (antistatic)
Country of Manufacture	United States
HS-Code	85159080900
Weight	0.1 kg



DESCRIPTION

The PM60MF375 micro fine tip from the Thermaltronics P series delivers heat precisely to the joint with a tip width of 0,25 mm. It operates in the 325 to 358 °C temperature range and is made for lead-free soldering.

KEY BENEFITS

- Micro fine with 0,25 mm tip width for a defined heat transfer
- Working range 325 to 358 °C (P series)
- Lead-free and RoHS compliant
- For the SHP-P, SHP-PM handpieces

TECHNICAL DATA

Manufacturer article no.	PM60MF375
Item no.	WL38083
Tip series	P (325 - 358 °C)
Tip shape	micro fine
Tip width	0,25 mm (0,01 in)
Tip length	13,4 mm (0,53 in)
Working temperature	325 - 358 °C

Compatible handpiece

SHP-P, SHP-PM

Type

lead-free, RoHS compliant

APPLICATIONS

Lead-free hand soldering and rework of printed circuit boards and electronic assemblies where a micro fine of 0,25 mm provides the right thermal contact area.

COMPATIBILITY AND SCOPE OF DELIVERY

Fits the SHP-P, SHP-PM handpieces of the Thermaltronics TMT-2000 soldering stations and the Oki MFR-PS1100, MFR-PS2200, MFR-PS1K and MFR-PS2K power units. Supplied as one piece.

RoHS compliant, lead-free. Country of origin USA.