

Soldering tip chisel 30° 1.8 mm (0.07 in) for P series - Thermaltronics PM75CP201

Item no. WL38108

Manufacturer Thermaltronics

Lead-free P series soldering tip, chisel shape, 1.8 mm wide (0.07 in), for the 350 to 398 °C working range. Fits the SHP-P and SHP-PM handpieces of the TMT-2000PS and Oki MFR-PS systems.

TECHNICAL DATA

Ausführungsklasse	ESD (antistatic)
Country of Manufacture	United States
HS-Code	85159080900
Weight	0.1 kg



STANDARDS & COMPLIANCE

ESD safe

DESCRIPTION

The chisel-shaped PM75CP201 soldering tip from the Thermaltronics P series delivers the cartridge heat right at the 1.8 mm wide tip, so joints in the 350 to 398 °C range form quickly and repeatably.

BENEFITS

- Chisel tip, 30°, 1.8 mm (0.07 in) wide for focused heat transfer
- Tip length 6.4 mm (0.25 in) for good access to the joint
- Fixed 350 to 398 °C working range
- Lead-free and RoHS compliant

TECHNICAL DATA

Item no.	WL38108
Manufacturer item no.	PM75CP201
Manufacturer	Thermaltronics
Product series	P soldering tip series
Temperature range	350 to 398 °C

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

Tip shape	chisel, 30°
Tip width	1.8 mm (0.07 in)
Tip length	6.4 mm (0.25 in)
Compatible handpiece	SHP-P, SHP-PM

APPLICATIONS

Lead-free hand and rework soldering of printed circuit boards in electronics manufacturing, prototyping and service.

COMPATIBILITY AND SCOPE OF DELIVERY

Fits the SHP-P and SHP-PM handpieces and the TMT-2000PS, TMT-2000S-PM stations as well as the Oki MFR-PS supply units (MFR-PS1100, MFR-PS2200, MFR-PS1300). Supplied as a single piece.

RoHS compliant, lead-free, ESD safe.