

Soldering tip conical 0.4 mm (0.02 in) for P series - Thermaltronics PM75CS152

Item no. WL38113

Manufacturer Thermaltronics

Lead-free P series soldering tip, conical shape, 0.4 mm wide (0.02 in), for the 350 to 398 °C working range. Fits the SHP-P and SHP-PM handpieces of the TMT-2000PS and Oki MFR-PS systems.

TECHNICAL DATA

Ausführungsklasse	ESD (antistatic)
Country of Manufacture	United States
HS-Code	85159080900
Weight	0.1 kg



STANDARDS & COMPLIANCE

ESD safe

DESCRIPTION

The conical-shaped PM75CS152 soldering tip from the Thermaltronics P series delivers the cartridge heat right at the 0.4 mm wide tip, so joints in the 350 to 398 °C range form quickly and repeatably.

BENEFITS

- Conical tip, 0.4 mm (0.02 in) wide for focused heat transfer
- Tip length 8.5 mm (0.33 in) for good access to the joint
- Fixed 350 to 398 °C working range
- Lead-free and RoHS compliant

TECHNICAL DATA

Item no.	WL38113
Manufacturer item no.	PM75CS152
Manufacturer	Thermaltronics
Product series	P soldering tip series
Temperature range	350 to 398 °C

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

Tip shape	conical
Tip width	0.4 mm (0.02 in)
Tip length	8.5 mm (0.33 in)
Compatible handpiece	SHP-P, SHP-PM

APPLICATIONS

Lead-free hand and rework soldering of printed circuit boards in electronics manufacturing, prototyping and service.

COMPATIBILITY AND SCOPE OF DELIVERY

Fits the SHP-P and SHP-PM handpieces and the TMT-2000PS, TMT-2000S-PM stations as well as the Oki MFR-PS supply units (MFR-PS1100, MFR-PS2200, MFR-PS1300). Supplied as a single piece.

RoHS compliant, lead-free, ESD safe.