

Soldering tip sharply bent 30° 0.4mm (0.016") - Thermaltronics PM75SB275

Item no. WL38130

Manufacturer Thermaltronics

Lead-free Thermaltronics P-series soldering tip, sharply bent 30° 0.4mm (0.016"), working range 350-398 °C. Fits SHP-P, SHP-PM handpiece and TMT-2000PS and MFR-PS series stations.

TECHNICAL DATA

Ausführungsklasse	ESD (antistatic)
Country of Manufacture	United States
HS-Code	85159080900
Weight	0.1 kg



DESCRIPTION

The Thermaltronics P-series sharply bent 30° 0.4mm (0.016") soldering tip is a lead-free replacement cartridge tip for precision soldering on TMT-2000PS and MFR-PS supply units and stations. Its 0,4 mm tip width suits the matching joint size within a working range of 350-398 °C.

KEY BENEFITS

- Tip width 0,4 mm mm (0,02 in) for controlled heat transfer
- Lead-free and RoHS compliant for modern SAC solder alloys
- P-series working temperature 350-398 °C

TECHNICAL DATA

Manufacturer item no.	PM75SB275
Item no.	WL38130
Series	P (350-398 °C)
Temperature range	350-398 °C
Tip width	0,4 mm (0,02 in)
Tip length	8,4 mm (0,33 in)
Tip shape	bent

APPLICATIONS

Hand soldering on PCBs and electronic assemblies, from fine-pitch work to larger joints depending on tip width.

COMPATIBILITY AND SCOPE OF DELIVERY

Fits handpiece SHP-P, SHP-PM. Suitable for: TMT-2000PS, MFR-PS1100, MFR-PS2200, MFR-PS1K, MFR-PS2K. Scope of delivery: 1 soldering tip.

RoHS compliant, lead-free. Origin: USA.