

Soldering tip sharply bent 30° 0.5mm (0.02") - Thermaltronics PM80SB276

Item no. WL38176

Manufacturer Thermaltronics

Soldering tip sharply bent 30° 0.5mm (0.02") from the Thermaltronics P series, lead-free and RoHS compliant. Temperature range 420 - 475 °C, tip width 0,5 mm. Fits handpiece SHP-P, SHP-PM.

TECHNICAL DATA

Ausführungsklasse **ESD (antistatic)**

Country of Manufacture **United States**

HS-Code **85159080900**

Weight **0.1 kg**


STANDARDS & COMPLIANCE

ESD safe

DESCRIPTION

Soldering tip sharply bent 30° 0.5mm (0.02") from the Thermaltronics P series for precise lead-free soldering. The tip operates in the 420 - 475 °C temperature range and is 0,5 mm wide, for repeatable joints on fine electronics. It is a direct replacement for the Metcal tip SCP-CNB05.

KEY BENEFITS

- Tip width 0,5 mm (0,02 in) for matched heat transfer
- 420 - 475 °C temperature range of the P series
- RoHS compliant and lead-free
- Fits handpiece SHP-P, SHP-PM

TECHNICAL DATA

Item no.	WL38176
Manufacturer no.	PM80SB276
Soldering tip series	P
Temperature range	420 - 475 °C

Tip width	0,5 mm (0,02 in)
Tip length	14 mm
Suitable handpiece	SHP-P, SHP-PM
Replaces Metcal	SCP-CNB05

APPLICATIONS

Suitable for SMD and THT soldering on printed circuit boards in repair, production and laboratory work.

COMPATIBILITY AND SCOPE OF DELIVERY

For use with handpiece SHP-P, SHP-PM and the power units TMT-2000PS, MFR-PS1100, MFR-PS2200, MFR-PS1K, MFR-PS2K. Supplied as a single piece.

RoHS compliant, lead-free, ESD-safe. Manufactured by Thermaltronics, USA.