

Soldering tip bevelled 45° 4,00mm (0,16") - Thermaltronics S75BV040

Item no. WL38227

Manufacturer Thermaltronics

Thermaltronics S-series soldering tip with 4 mm tip width and working temperature 350-398 °C for precise lead-free soldering. Fits the SHP-SM handpiece and the TMT-2000PS, SP200, MFR-PS1100, MFR-PS2200 control units. RoHS compliant and lead-free.

TECHNICAL DATA

Ausführungsklasse	ESD (antistatic)
Country of Manufacture	United States
HS-Code	85159080900
Weight	0.1 kg



STANDARDS & COMPLIANCE

ESD safe

DESCRIPTION

The S75BV040 soldering tip from the Thermaltronics S-series delivers repeatable results in lead-free hand soldering, with a tip width of 4 mm and a working temperature range of 350-398 °C. SmartHeat technology controls the tip temperature without external calibration.

BENEFITS

- Tip width 4 mm (0,16 in) for bevelled joints.
- Working temperature 350-398 °C, set by the tip with no separate adjustment.
- RoHS compliant and lead-free.

TECHNICAL DATA

Manufacturer	Thermaltronics
Model	S75BV040
Manufacturer item no.	S75BV040
Item no.	WL38227
Product series	S soldering tip series

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

Temperature range	350-398 °C
Tip width	4 mm (0,16 in)
Tip length	17 mm (0,67 in)
Tip alignment	abgeschrägt
Suitable handpiece	SHP-SM
Suitable control unit	TMT-2000PS, SP200, MFR-PS1100, MFR-PS2200

APPLICATIONS

Suitable for electronics repair and production work, from soldering individual components to through-hole and SMD joints depending on tip geometry.

COMPATIBILITY AND SCOPE OF DELIVERY

Fits the Thermaltronics SHP-SM handpiece (TMT-2000S station) and Metcal MFR-H6-SSC (MFR-1160, MFR-1161 and SP200 station). Suitable for the TMT-2000PS, SP200, MFR-PS1100, MFR-PS2200 supply units (SSC tips). Supplied as a single tip (1 piece).

RoHS compliant, lead-free, ESD-safe. Country of origin USA.