

Lead-free soldering tip bevelled 45° 5.00mm (0.20") series S - Thermaltronics S75BV050

Item no. WL38228

Manufacturer Thermaltronics

Lead-free series S soldering tip for Thermaltronics SHP-SM and Metcal MFR-H6-SSC handpieces, bevelled geometry 45° with 5.00mm width. Working temperature range 350 to 398 °C, RoHS compliant and lead-free.

TECHNICAL DATA

Ausführungsklasse	ESD (antistatic)
Country of Manufacture	United States
HS-Code	85159080900
Weight	0.1 kg



STANDARDS & COMPLIANCE

ESD safe

DESCRIPTION

The S75BV050 soldering tip from the Thermaltronics series S provides a bevelled tip geometry with a 45° angle and 5.00mm tip width for precise lead-free soldering on electronic assemblies. It operates across a 350 to 398 °C temperature range.

BENEFITS

- Bevelled geometry 45° with 5.00mm width for efficient heat transfer
- Working temperature range 350 to 398 °C for repeatable lead-free joints
- RoHS compliant and lead-free

TECHNICAL DATA

Item no.	WL38228
Model	S75BV050
Manufacturer item no.	S75BV050
Product series	S, 350 - 398 °C
Temperature range	350 - 398 °C

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

Tip length	15 mm mm
Tip width	5,00mm (0,20")
Tip geometry	bevelled 45°
Compatible handpiece	SHP-SM
Compatible control unit	TMT-2000PS, SP200, MFR-PS1100, MFR-PS2200
Dimensions with packaging (LxWxH)	174 mm x 35 mm x 12 mm

APPLICATIONS

- Lead-free hand soldering and touch-up in electronics manufacturing
- Repair and rework of printed circuit boards and components

COMPATIBILITY AND SCOPE OF DELIVERY

Suitable for the Thermaltronics SHP-SM handpiece (TMT-2000S station) and the Metcal MFR-H6-SSC (MFR-1160, MFR-1161 and SP200 station). Compatible power units: TMT-2000PS, SP200, MFR-PS1100 and MFR-PS2200 (SSC tips). Supplied as a single piece.

RoHS compliant, lead-free, suitable for ESD-safe work. Country of origin USA.