

Soldering tip Micro Fine 0,25mm (0,01"), lead-free, S series - Thermaltronics S75MF003

Item no. WL38260

Manufacturer Thermaltronics

Lead-free S series soldering tip, tip width 0,25 mm, working temperature 350 to 398 °C. Fits the Thermaltronics SHP-SM handpiece and the TMT-2000PS, SP200, MFR-PS1100 and MFR-PS2200 supply units. Replaces Metcal SSC-790A.

TECHNICAL DATA

Ausführungsklasse **ESD (antistatic)**

Country of Manufacture **United States**

HS-Code **85159080900**

Weight **0.1 kg**


STANDARDS & COMPLIANCE

ESD safe

DESCRIPTION

The S75MF003 soldering tip from the Thermaltronics S series is a lead-free replacement tip with a 0,25 mm tip width for fine to medium soldering work on printed circuit boards. It runs in the 350 to 398 °C range using SmartHeat technology with no separate temperature setting.

KEY BENEFITS

- 0,25 mm tip width for precise joints
- Stable working temperature of 350 to 398 °C
- RoHS compliant and lead-free
- Quick change via the SHP-SM handpiece
- Replaces Metcal article no. SSC-790A

TECHNICAL DATA

Manufacturer item no.	S75MF003
Item no.	WL38260
Series	S

Tip width	0,25 mm
Tip length	13,6 mm
Tip shape	Micro Fine / micro fine
Temperature range	350 - 398 °C
Type	Lötspitze / soldering tip / panne à souder
Replaces Metcal	SSC-790A

APPLICATIONS

Suited to soldering and rework of SMD and through-hole components in electronics manufacturing, repair and laboratory work.

COMPATIBILITY AND SCOPE OF SUPPLY

Fits the Thermaltronics SHP-SM handpiece (TMT-2000S station) and Metcal MFR-H6-SSC. Suitable supply units: TMT-2000PS, SP200, MFR-PS1100 and MFR-PS2200. Supplied as one piece.

RoHS compliant, lead-free, ESD safe.