

Soldering tip conical 1,4 mm, RoHS lead-free for SHP-SM - Thermaltronics S80CS014

Item no. WL38296

Manufacturer Thermaltronics

Replaceable S-series soldering tip in conical shape with 1,4 mm tip width (0,055 in) and 15,4 mm tip length. Working temperature range 420 to 475 °C, RoHS-compliant and lead-free. Fits the SHP-SM handpiece and the control units TMT-2000PS, SP200, MFR-PS1100, MFR-PS2200.

TECHNICAL DATA

Ausführungsklasse **ESD (antistatic)**

Country of Manufacture **United States**

HS-Code **85159080900**

Weight **0.1 kg**


STANDARDS & COMPLIANCE

ESD safe

DESCRIPTION

The Thermaltronics S80CS014 is a lead-free S-series soldering tip for precise soldering on printed circuit boards and electronic assemblies. The conical tip with 1,4 mm width (0,055 in) transfers heat in a targeted way and works across the 420 to 475 °C temperature range.

BENEFITS

- Conical tip shape, tip width 1,4 mm (0,055 in)
- Tip length 15,4 mm (0,61 in) for good access to the joint
- Working temperature range 420 to 475 °C
- RoHS-compliant and lead-free
- Replaces Metcal article no. SSC-874A

TECHNICAL DATA

Manufacturer item no.	S80CS014
Item no.	WL38296
Series	S soldering tip series, 420 to 475 °C

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

Tip shape	conical
Tip width	1,4 mm (0,055 in)
Tip length	15,4 mm (0,61 in)
Type	soldering tip
Replaces Metcal	SSC-874A

APPLICATIONS

Suitable for hand and touch-up soldering in electronics manufacturing, repair and prototyping, particularly with lead-free solders.

COMPATIBILITY AND SCOPE OF DELIVERY

Fits the SHP-SM soldering handpiece (Thermaltronics TMT-2000S) and Metcal MFR-H6-SSC (MFR-1160, MFR-1161 and SP200). Suitable control units: TMT-2000PS, SP200, MFR-PS1100, MFR-PS2200. Scope of delivery: 1 soldering tip.

RoHS-compliant, lead-free, ESD-safe handling.