

ESD coiled cord, 2 MOhm, 3/10 mm snap, 1.8 m, black - Safeguard WL42078

Item no. WL42078**Manufacturer Safeguard**

ESD grounding cord for personnel grounding in the EPA. 3 mm snap for the wrist strap, 10 mm snap to the ground point, extends to 1.8 m. Built-in 2 MOhm safety resistor.

TECHNICAL DATA

Ausführungsklasse	ESD (antistatic)
Colour	Black
Norm	IEC 61340-5-1
Sales unit	1 Stück
Weight	0.1 kg



STANDARDS & COMPLIANCE

ESD safe IEC 61340-5-1

DESCRIPTION

This ESD coiled cord connects an ESD wrist strap to the ground point of the bench mat or the common ground bar and drains charges in a controlled way. It is intended for personnel grounding in the EPA in line with IEC 61340-5-1.

BENEFITS

- Built-in 2 MOhm safety resistor limits the discharge current
- Compact version with 1.8 m reach
- 3 mm snap for the wrist strap and 10 mm snap for the ground side

TECHNICAL DATA

- Electrical resistance: 2 MOhm
- Extended length: 1800 mm
- Connection: 3 mm snap / 10 mm snap
- Colour: black
- Selling unit: 1 piece

APPLICATIONS

For assembly, testing and repair of electronic assemblies at the ESD workstation.

STANDARDS AND COMPLIANCE

Suitable for grounding to IEC 61340-5-1, tested to BGI 818:2001.