

Alsident 100-5545-3-5. Extraction arm system DN100 for wall/ceiling mounting, 3 joints, 1185 mm, white

Item no. WL42480

Manufacturer Alsident

Extraction arm system DN100 for wall/ceiling mounting, 3 joints, 1185 mm, white

TECHNICAL DATA

Colour **White**

Weight **0.1 kg**



DESCRIPTION

The Alsident DN 100 extraction system is particularly suitable for larger quantities of pollutants or larger collection tasks. The pipes have a diameter of 100 mm and the recommended air volume for the extraction is between 140 m³/h and 400 m³/h.

- with 2 gas springs
- Maintenance-free O-rings made of polyethylene (PE)
- Integrated throttle valve which is in open position from the air flow to ensure maximum flow through the unit
- Threaded rods, springs and thumbscrews in acid-resistant stainless steel (AISI 316L)
- Acid-resistant POP® rivets for increased durability even when used in aggressive environments
- Protective grille (accessory) to prevent foreign bodies from being sucked in
- Components RoHS compliant

PRODUCT DETAILS

item number	WL42480
model	100-5545-3-5
manufacturer	ALSIDENT
manufacturer item number	100-5545-3-5
order unit	piece

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

material	Anodised aluminium tubes - layer thickness 10μ, joints made of impact-resistant, chemically resistant polypropylene (PP)
product series	Alsident System 100 AL
joint colour	white
assembling	ceiling mounting, wall mounting
air volume extraction arm	140–400 m³/h
range	1185 mm
diameter of tube	100 mm
number of joints	3
ESD safe	no