

KilewsESD electric screwdriver with lever start, 0.008 - 0.14 Nm

Item no. WL42680

Manufacturer Kilews

ESD electric screwdriver with lever start, 0.008 - 0.14 Nm

TECHNICAL DATA

Ausführungsklasse **ESD (antistatic)**Weight **0.1 kg**

STANDARDS & COMPLIANCE

ESD safe

DESCRIPTION

- Low weight
- High stability
- Easy to use
- Quiet operation
- Simple change of direction with anticlockwise button
- No carbon dust is output - making it suitable for clean room workstations
- Brushless
- Voltage: 9/12V DC
- Output: 25 W
- Torque: Nm 0.008 - 0.14
- Accuracy: +/- 3%
- Torque setting: infinite
- Idle speed: HI 280 min, LO 200 min
- Screw size, threaded screw: 1.0-1.7 / self-tapping: 1.0-1.5
- Weight: 170 g
- Length: 165 mm
- Lever start, including torque sleeve

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

PRODUCT DETAILS

item number	WL42680
model	SKD-B100LS4-ESD
manufacturer	KILEWS
order unit	piece
ESD safe	yes