

Knipex 95 11 200. Cable shears with double cutting edge, with anti-trap protection, plastic-coated handles, 20 mm / 70 mm², 200 mm

Item no. WL43372

Manufacturer Knipex

Cable shears with double cutting edge, with anti-trap protection, plastic-coated handles, Ø 20 mm / 70 mm², 200 mm

TECHNICAL DATA

Weight

0.1 kg



DESCRIPTION

For cutting Cu and Al cables. Not suitable for steel wire and hard-drawn copper conductors. Hardened cutting edges with precision grinding. Cuts smoothly and cleanly without crushing. By dividing the cutting process into pre-cut (insulating jacket in the front cutting area) and post-cut (conductor in the rear cutting area), cables up to Ø 20 mm can be cut in one-hand operation. Low power requirement due to favourable transmission ratios and special cutting geometry. Pinch protection prevents crushing injuries. Adjustable screw joint, self-locking. - Cutting value Cu-cable, stranded: 70mm² - Cutting value Cu-cable, stranded: Ø 20mm - AWG: 2 / 0

- For cutting Cu and Al cables
- Not suitable for steel wire and hard drawn copper conductors
- Hardened cutting edges with precision grinding
- Cuts smoothly and cleanly without crushing
- By dividing the cutting process into pre-cut (insulating sheath in the front cutting area) and post-cut (conductor in the rear cutting area), cables up to Ø 20 mm can be cut in one-hand operation
- Low power requirement due to favourable transmission ratios and special cutting geometry
- Pinch protection prevents crushing injuries
- Adjustable screw joint, self-locking

PRODUCT DETAILS

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

item number	WL43372
model	95 11 200
manufacturer	KNIPEX
manufacturer item number	95 11 200
dimensions (LxWxH)	200 mm x 21 mm x 15 mm
dimensions with packaging (LxWxH)	236 mm x 88 mm x 52 mm
Packaging volume	1.08 dm ³
order unit	piece
type of packaging	single pack
RoHS conform	no
surface	burnished
VDE	no
ESD safe	no
tool length	200 mm
AWG	2 / 0
type of handle	Covered with plastic
type of shears	cable shears
Cutting value copper cable, multistranded	70 mm ²
Cutting value copper cable, multistranded (diameter)	20 mm