

Knipex 00 21 20. Tool case "Vision24" electric, 24 pieces

Item no. WL50858

Manufacturer Knipex

Tool case "Vision24" electric, 24 pieces

TECHNICAL DATA

Weight

0.1 kg



STANDARDS & COMPLIANCE

DIN EN 60900

DESCRIPTION

Tool case "Vision24" Elektro equipped with 20 branded tools, partly VDE-tested according to DIN EN 60900. Max. load: 20 kg. Max. load: 20 kg. 24 litre capacity. Flexible design options thanks to individually divisible inserts in the 60 mm deep base tray and its cover panel with six large tool pockets. Sturdy latching hinges keep the lid open when needed, despite the weight of the tools themselves. Sturdy, ergonomic carrying handle, locks into place at a 90° angle. Removable tool panel with 15 tool pockets on the bottom side and six tool pockets and a clamp compartment (400 mm wide) on the lid side, held open by a push button. Two lockable steel tilt locks protect case contents from theft. All-round double aluminium frame. Durable ABS material, black. Cover and tool panels made of dirt-repellent PP hollow chamber panels. Dimensions, outside (W x H x D): 480 x 380 x 180 mm Dimensions, inside (W x H x D): 460 x 310 x 170 mm. - Dimension width, outside (inside): 480mm 460mm - Dimension height, outside (inside): 380mm 310mm - Dimension depth, outside (inside): 180mm 170mm Scope of delivery: 1 x 12 40 200 KNIPEX self-adjusting wire stripper (0.03 - 10.0 mm²), 1 x 86 03 180 KNIPEX pliers wrench pliers and wrench in one tool, 1 x 86 03 180 KNIPEX pliers wrench pliers and wrench in one tool, 1 x 98 52 KNIPEX cable knife, 1 x 95 16 200 KNIPEX cable shears with double cutting edge (Ø 20 mm / 70 mm²), 1 x 03 06 180 KNIPEX combination pliers (for flat and round material), 1 x 87 03 250 KNIPEX Cobra® high-tech water pump pliers, 1 x 98 24

01 SL KNIPEX screwdriver (Slim) for Phillips® cross-slotted head screws (PH1), 1 x 98 24 02 SL KNIPEX screwdriver (Slim) for Phillips® cross-slotted head screws (PH2), 1 x 98 25 01 SL KNIPEX screwdriver (Slim) for cross-slotted head screws Pozidriv® (PZ 1), 1 x 98 25 02 SL KNIPEX screwdriver (Slim) for cross-slotted head screws Pozidriv® (PZ 2), 1 x 98 20 25 KNIPEX screwdriver for slotted screws (2.5 mm), 1 x 98 20 40 SL KNIPEX screwdriver (Slim) for slotted screws (4.0 mm), 1 x 98 20 55 SL KNIPEX screwdriver (Slim) for slotted screws (5,5 mm), 1 x 98 20 65 SL KNIPEX Screwdriver (Slim) for slotted screws (6.5 mm), 1 x 16 95 01 SB KNIPEX ErgoStrip® Universal stripping tool (Ø 8.0 - 13,0 mm), 1 x 70 06 160 KNIPEX side cutters, 1 x 74 06 160 KNIPEX power side cutters (ideal for all types of wire), 1 x 26 16 200 KNIPEX flat round nose pliers with cutting edge (Stork nose pliers) (For narrow working areas), 1 x 26 26 200 KNIPEX flat round nose pliers with cutting edge (Stork nose pliers) (For narrow working areas), 1 x 005655 Wera voltage tester, single pole 247 (0.5 x 3.0 x 70 mm),

- Flexible design options thanks to individually divisible inserts in the 60 mm deep base tray and its cover panel with six large tool pockets
- Sturdy latching hinges keep the lid open when required, despite the weight of the tools themselves
- Sturdy, ergonomic carrying handle, locks into place at a 90° angle
- Removable tool panel with 15 tool pockets on the bottom side and six tool pockets as well as a clamp compartment (400 mm wide) on the lid side, held in place by a push button
- Two lockable steel tilt locks protect the case contents from theft
- All-round double aluminium frame
- Hard-wearing design made of ABS material, black
- Cover and tool panels made of dirt-repellent PP hollow chamber panels
- Dimensions, outside (W x H x D): 480 x 380 x 180 mm Dimensions, inside (W x H x D): 460 x 310 x 170 mm

PRODUCT DETAILS

item number	WL50858
model	00 21 20
manufacturer	KNIPEX
manufacturer item number	00 21 20
dimensions (LxWxH)	484 mm x 176 mm x 372 mm
dimensions with packaging (LxWxH)	512 mm x 204 mm x 401 mm
Packaging volume	41.797 dm³

scope of supply

1 x 03 06 180

1 x 12 40 200

1 x 16 95 01 SB /

1 x 26 16 200

1 x 26 26 200

1 x 70 06 160

1 x 74 06 200

1 x 86 03 180

1 x 87 03 250

1 x 95 16 200

1 x 98 20 25

1 x 98 20 40 SL

1 x 98 20 55 SL /

1 x 98 20 65 SL

1 x 98 24 01 SL /

1 x 98 24 02 SL

1 x 98 25 01 SL /

1 x 98 25 02 SL

1 x 98 52

1 x 03 06 180 /

1 x 12 40 200

1 x 16 80 125 /

1 x 26 16 200 /1 x 26 26 200 /

1 x 70 06 160

1 x 74 06 200 /

1 x 86 03 180

1 x 87 03 250 /

1 x 95 16 200

1 x 98 56

order unit

piece

product series

Vision24

RoHS conform

no

VDE

no