

Bahco NSB006-3034. Non-sparking double open-end wrench, 30x34 mm, made of copper beryllium, 270 mm

Item no. WL52817

Manufacturer Bahco

Non-sparking double open-end wrench, 30x34 mm, made of copper beryllium, 270 mm

TECHNICAL DATA

Weight

0.1 kg



STANDARDS & COMPLIANCE

DIN 895

DESCRIPTION

OTHER VERSIONS

item number	length	wrench width
WL52769	92 mm	6 mm / 7 mm
WL52770	95 mm	7 mm / 9 mm
WL52771	96 mm	8 mm / 9 mm
WL52772	96 mm	1 mm / 9 mm
WL52773	100 mm	10 mm / 11 mm
WL52774	100 mm	10 mm / 12 mm
WL52775	110 mm	12 mm / 14 mm
WL52776	110 mm	13 mm / 15 mm
WL52777	115 mm	14 mm / 17 mm
WL52778	120 mm	16 mm / 18 mm
WL52779	124 mm	17 mm / 19 mm

item number	length	wrench width
WL52780	124 mm	17 mm / 22 mm
WL52781	128 mm	18 mm / 19 mm
WL52782	130 mm	19 mm / 21 mm
WL52783	128 mm	19 mm / 22 mm
WL52784	130 mm	20 mm / 22 mm
WL52785	133 mm	21 mm / 23 mm
WL52786	145 mm	22 mm / 24 mm
WL52787	150 mm	24 mm / 27 mm
WL52788	150 mm	25 mm / 28 mm
WL52789	157 mm	26 mm / 28 mm
WL52790	163 mm	27 mm / 30 mm
WL52791	170 mm	27 mm / 32 mm
WL52792	173 mm	30 mm / 32 mm
WL52793	175 mm	30 mm / 36 mm
WL52794	175 mm	32 mm / 36 mm
WL52795	182 mm	36 mm / 41 mm
WL52796	185 mm	41 mm / 46 mm
WL52797	190 mm	46 mm / 50 mm
WL52798	195 mm	6 mm / 7 mm
WL52799	200 mm	8 mm / 9 mm
WL52800	200 mm	10 mm / 11 mm
WL52801	210 mm	12 mm / 13 mm
WL52802	210 mm	14 mm / 15 mm
WL52803	215 mm	16 mm / 17 mm
WL52804	220 mm	18 mm / 19 mm
WL52805	230 mm	20 mm / 22 mm
WL52806	230 mm	21 mm / 23 mm
WL52807	230 mm	24 mm / 26 mm
WL52808	233 mm	25 mm / 28 mm
WL52809	236 mm	27 mm / 29 mm
WL52810	250 mm	30 mm / 32 mm
WL52811	250 mm	27 mm / 29 mm
WL52812	250 mm	27 mm / 30 mm
WL52813	243 mm	27 mm / 32 mm
WL52814	250 mm	28 mm / 30 mm

item number	length	wrench width
WL52815	265 mm	30 mm / 31 mm
WL52816	265 mm	30 mm / 32 mm
WL52817	270 mm	30 mm / 34 mm
WL52818	270 mm	30 mm / 36 mm
WL52819	270 mm	32 mm / 34 mm
WL52820	300 mm	32 mm / 35 mm
WL52821	300 mm	32 mm / 36 mm
WL52822	300 mm	33 mm / 35 mm
WL52823	300 mm	34 mm / 36 mm
WL52824	300 mm	35 mm / 36 mm
WL52825	330 mm	36 mm / 38 mm
WL52826	330 mm	36 mm / 41 mm
WL52827	330 mm	38 mm / 42 mm
WL52828	360 mm	41 mm / 46 mm
WL52829	370 mm	46 mm / 50 mm
WL52830	375 mm	50 mm / 52 mm
WL52831	385 mm	50 mm / 55 mm
WL52832	400 mm	50 mm / 60 mm
WL52833	400 mm	50 mm / 62 mm
WL52834	415 mm	55 mm / 60 mm
WL52835	435 mm	60 mm / 65 mm
WL52836	480 mm	65 mm / 70 mm

Non-sparking tools are used in areas where there is a potential fire and explosion hazard due to flying sparks. Double open ended wrench, 30 x 34 mm, made of copper beryllium, 270 mm.

- Made of copper beryllium
- Head angle: 15°
- Double open-end wrench, with two different widths
- Meets the product standards according to DIN 895
- Non-sparking tools are used in areas where there is a potential fire and explosion hazard due to flying sparks
- Head angle of 15° for working in areas difficult to access
- Antimagnetic, extremely corrosion resistant

PRODUCT DETAILS

item number	WL52817
model	NSB006-3034

manufacturer	BAHCO
manufacturer item number	NSB006-3034
dimensions (LxWxH)	270 mm x 144 mm x 38 mm
order unit	piece
ESD safe	no
Type open-end spanner	Double open-end spanner
tool material	amagnetic steel, copperberyllium
packaging mass	piece
VDE	no