

## Bahco NSB006-3642. Non-sparking double open-end wrench, 38x42 mm, made of copper beryllium, 330 mm

Item no. WL52827

Manufacturer Bahco

Non-sparking double open-end wrench, 38x42 mm, made of copper beryllium, 330 mm

### TECHNICAL DATA

Weight

0.1 kg



### STANDARDS & COMPLIANCE

DIN 895

### DESCRIPTION

### OTHER VERSIONS

| item number             | length | wrench width  |
|-------------------------|--------|---------------|
| <a href="#">WL52769</a> | 92 mm  | 6 mm / 7 mm   |
| <a href="#">WL52770</a> | 95 mm  | 7 mm / 9 mm   |
| <a href="#">WL52771</a> | 96 mm  | 8 mm / 9 mm   |
| <a href="#">WL52772</a> | 96 mm  | 1 mm / 9 mm   |
| <a href="#">WL52773</a> | 100 mm | 10 mm / 11 mm |
| <a href="#">WL52774</a> | 100 mm | 10 mm / 12 mm |
| <a href="#">WL52775</a> | 110 mm | 12 mm / 14 mm |
| <a href="#">WL52776</a> | 110 mm | 13 mm / 15 mm |
| <a href="#">WL52777</a> | 115 mm | 14 mm / 17 mm |
| <a href="#">WL52778</a> | 120 mm | 16 mm / 18 mm |
| <a href="#">WL52779</a> | 124 mm | 17 mm / 19 mm |

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/4

| item number             | length | wrench width  |
|-------------------------|--------|---------------|
| <a href="#">WL52780</a> | 124 mm | 17 mm / 22 mm |
| <a href="#">WL52781</a> | 128 mm | 18 mm / 19 mm |
| <a href="#">WL52782</a> | 130 mm | 19 mm / 21 mm |
| <a href="#">WL52783</a> | 128 mm | 19 mm / 22 mm |
| <a href="#">WL52784</a> | 130 mm | 20 mm / 22 mm |
| <a href="#">WL52785</a> | 133 mm | 21 mm / 23 mm |
| <a href="#">WL52786</a> | 145 mm | 22 mm / 24 mm |
| <a href="#">WL52787</a> | 150 mm | 24 mm / 27 mm |
| <a href="#">WL52788</a> | 150 mm | 25 mm / 28 mm |
| <a href="#">WL52789</a> | 157 mm | 26 mm / 28 mm |
| <a href="#">WL52790</a> | 163 mm | 27 mm / 30 mm |
| <a href="#">WL52791</a> | 170 mm | 27 mm / 32 mm |
| <a href="#">WL52792</a> | 173 mm | 30 mm / 32 mm |
| <a href="#">WL52793</a> | 175 mm | 30 mm / 36 mm |
| <a href="#">WL52794</a> | 175 mm | 32 mm / 36 mm |
| <a href="#">WL52795</a> | 182 mm | 36 mm / 41 mm |
| <a href="#">WL52796</a> | 185 mm | 41 mm / 46 mm |
| <a href="#">WL52797</a> | 190 mm | 46 mm / 50 mm |
| <a href="#">WL52798</a> | 195 mm | 6 mm / 7 mm   |
| <a href="#">WL52799</a> | 200 mm | 8 mm / 9 mm   |
| <a href="#">WL52800</a> | 200 mm | 10 mm / 11 mm |
| <a href="#">WL52801</a> | 210 mm | 12 mm / 13 mm |
| <a href="#">WL52802</a> | 210 mm | 14 mm / 15 mm |
| <a href="#">WL52803</a> | 215 mm | 16 mm / 17 mm |
| <a href="#">WL52804</a> | 220 mm | 18 mm / 19 mm |
| <a href="#">WL52805</a> | 230 mm | 20 mm / 22 mm |
| <a href="#">WL52806</a> | 230 mm | 21 mm / 23 mm |
| <a href="#">WL52807</a> | 230 mm | 24 mm / 26 mm |
| <a href="#">WL52808</a> | 233 mm | 25 mm / 28 mm |
| <a href="#">WL52809</a> | 236 mm | 27 mm / 29 mm |
| <a href="#">WL52810</a> | 250 mm | 30 mm / 32 mm |
| <a href="#">WL52811</a> | 250 mm | 27 mm / 29 mm |
| <a href="#">WL52812</a> | 250 mm | 27 mm / 30 mm |
| <a href="#">WL52813</a> | 243 mm | 27 mm / 32 mm |
| <a href="#">WL52814</a> | 250 mm | 28 mm / 30 mm |

| item number             | length        | wrench width         |
|-------------------------|---------------|----------------------|
| <a href="#">WL52815</a> | 265 mm        | 30 mm / 31 mm        |
| <a href="#">WL52816</a> | 265 mm        | 30 mm / 32 mm        |
| <a href="#">WL52817</a> | 270 mm        | 30 mm / 34 mm        |
| <a href="#">WL52818</a> | 270 mm        | 30 mm / 36 mm        |
| <a href="#">WL52819</a> | 270 mm        | 32 mm / 34 mm        |
| <a href="#">WL52820</a> | 300 mm        | 32 mm / 35 mm        |
| <a href="#">WL52821</a> | 300 mm        | 32 mm / 36 mm        |
| <a href="#">WL52822</a> | 300 mm        | 33 mm / 35 mm        |
| <a href="#">WL52823</a> | 300 mm        | 34 mm / 36 mm        |
| <a href="#">WL52824</a> | 300 mm        | 35 mm / 36 mm        |
| <a href="#">WL52825</a> | 330 mm        | 36 mm / 38 mm        |
| <a href="#">WL52826</a> | 330 mm        | 36 mm / 41 mm        |
| <b>WL52827</b>          | <b>330 mm</b> | <b>38 mm / 42 mm</b> |
| <a href="#">WL52828</a> | 360 mm        | 41 mm / 46 mm        |
| <a href="#">WL52829</a> | 370 mm        | 46 mm / 50 mm        |
| <a href="#">WL52830</a> | 375 mm        | 50 mm / 52 mm        |
| <a href="#">WL52831</a> | 385 mm        | 50 mm / 55 mm        |
| <a href="#">WL52832</a> | 400 mm        | 50 mm / 60 mm        |
| <a href="#">WL52833</a> | 400 mm        | 50 mm / 62 mm        |
| <a href="#">WL52834</a> | 415 mm        | 55 mm / 60 mm        |
| <a href="#">WL52835</a> | 435 mm        | 60 mm / 65 mm        |
| <a href="#">WL52836</a> | 480 mm        | 65 mm / 70 mm        |

Non-sparking tools are used in areas where there is a potential fire and explosion hazard due to flying sparks. Double open ended wrench, 38 x 42 mm, made of copper beryllium, 330 mm.

- Made of copper beryllium
- Head angle: 15°
- Double open-end wrench, with two different widths
- Meets the product standards according to DIN 895
- Non-sparking tools are used in areas where there is a potential fire and explosion hazard due to flying sparks
- Head angle of 15° for working in areas difficult to access
- Antimagnetic, extremely corrosion resistant

## PRODUCT DETAILS

|             |             |
|-------------|-------------|
| item number | WL52827     |
| model       | NSB006-3642 |

|                          |                                  |
|--------------------------|----------------------------------|
| manufacturer             | BAHCO                            |
| manufacturer item number | NSB006-3642                      |
| dimensions (LxWxH)       | 330 mm x 164 mm x 38 mm          |
| order unit               | piece                            |
| ESD safe                 | no                               |
| Type open-end spanner    | Double open-end spanner          |
| tool material            | amagnetic steel, copperberyllium |
| packaging mass           | piece                            |
| VDE                      | no                               |