

Bahco NSB011-1617. Non-sparking, deep-cranked double ring spanner, 16x17 mm, made of copper beryllium, 220 mm

Item no. WL52871

Manufacturer Bahco

Non-sparking, deep-cranked double ring spanner, 16x17 mm, made of copper beryllium, 220 mm

TECHNICAL DATA

Weight 0.1 kg



STANDARDS & COMPLIANCE

DIN 837

DESCRIPTION

OTHER VERSIONS

item number	length	wrench width
WL52867	130 mm	8 mm / 9 mm
WL52868	140 mm	10 mm / 11 mm
WL52869	160 mm	12 mm / 13 mm
WL52870	200 mm	14 mm / 15 mm
WL52871	220 mm	16 mm / 17 mm
WL52872	255 mm	18 mm / 19 mm
WL52873	285 mm	20 mm / 22 mm
WL52874	285 mm	21 mm / 23 mm
WL52875	340 mm	24 mm / 26 mm
WL52876	350 mm	25 mm / 28 mm
WL52877	365 mm	27 mm / 29 mm

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

item number	length	wrench width
WL52878	390 mm	30 mm / 32 mm

Non-sparking tools are used in areas where there is a potential fire and explosion hazard due to flying sparks. Non-sparking, deep-cranked double ring spanner, 16 x 17 mm, made of copper beryllium, 220 mm.

- Made of copper beryllium
- Double ring spanner with two different key widths
- Ideal for confined spaces and indentations
- Meets the product standards according to DIN 837
- Non-sparking tools are used in areas where there is a potential fire and explosion hazard due to flying sparks
- Antimagnetic, extremely corrosion resistant

PRODUCT DETAILS

item number	WL52871
model	NSB011-1617
manufacturer	BAHCO
manufacturer item number	NSB011-1617
dimensions (LxWxH)	220 mm x 28 mm x 30 mm
order unit	piece
ESD safe	no
Ring spanner Type	Doppler ring key
tool material	amagnetic steel, copperberyllium
packaging mass	piece
VDE	no