

## Bahco NSB100-46. Non-sparking 46 mm impact open-end wrench made of copper beryllium, 250 mm

Item no. WL52903

Manufacturer Bahco

Non-sparking 46 mm impact open-end wrench made of copper beryllium, 250 mm

### TECHNICAL DATA

Weight

0.1 kg



### DESCRIPTION

### OTHER VERSIONS

| item number             | length | wrench width |
|-------------------------|--------|--------------|
| <a href="#">WL52879</a> | 485 mm | 100 mm       |
| <a href="#">WL52880</a> | 485 mm | 105 mm       |
| <a href="#">WL52881</a> | 513 mm | 110 mm       |
| <a href="#">WL52882</a> | 513 mm | 115 mm       |
| <a href="#">WL52883</a> | 530 mm | 120 mm       |
| <a href="#">WL52884</a> | 125 mm | 17 mm        |
| <a href="#">WL52885</a> | 125 mm | 19 mm        |
| <a href="#">WL52886</a> | 135 mm | 22 mm        |
| <a href="#">WL52887</a> | 150 mm | 24 mm        |
| <a href="#">WL52888</a> | 150 mm | 25 mm        |
| <a href="#">WL52889</a> | 175 mm | 27 mm        |
| <a href="#">WL52890</a> | 175 mm | 28 mm        |
| <a href="#">WL52891</a> | 190 mm | 29 mm        |
| <a href="#">WL52892</a> | 190 mm | 30 mm        |

| item number             | length        | wrench width |
|-------------------------|---------------|--------------|
| <a href="#">WL52893</a> | 190 mm        | 32 mm        |
| <a href="#">WL52894</a> | 190 mm        | 33 mm        |
| <a href="#">WL52895</a> | 200 mm        | 34 mm        |
| <a href="#">WL52896</a> | 210 mm        | 35 mm        |
| <a href="#">WL52897</a> | 210 mm        | 36 mm        |
| <a href="#">WL52898</a> | 210 mm        | 37 mm        |
| <a href="#">WL52899</a> | 220 mm        | 38 mm        |
| <a href="#">WL52900</a> | 230 mm        | 41 mm        |
| <a href="#">WL52901</a> | 230 mm        | 42 mm        |
| <a href="#">WL52902</a> | 250 mm        | 45 mm        |
| <b>WL52903</b>          | <b>250 mm</b> | <b>46 mm</b> |
| <a href="#">WL52904</a> | 250 mm        | 47 mm        |
| <a href="#">WL52905</a> | 275 mm        | 50 mm        |
| <a href="#">WL52906</a> | 275 mm        | 52 mm        |
| <a href="#">WL52907</a> | 305 mm        | 54 mm        |
| <a href="#">WL52908</a> | 305 mm        | 55 mm        |
| <a href="#">WL52909</a> | 305 mm        | 56 mm        |
| <a href="#">WL52910</a> | 315 mm        | 58 mm        |
| <a href="#">WL52911</a> | 315 mm        | 60 mm        |
| <a href="#">WL52912</a> | 335 mm        | 63 mm        |
| <a href="#">WL52913</a> | 335 mm        | 65 mm        |
| <a href="#">WL52914</a> | 335 mm        | 67 mm        |
| <a href="#">WL52915</a> | 370 mm        | 70 mm        |
| <a href="#">WL52916</a> | 370 mm        | 71 mm        |
| <a href="#">WL52917</a> | 375 mm        | 75 mm        |
| <a href="#">WL52918</a> | 375 mm        | 77 mm        |
| <a href="#">WL52919</a> | 400 mm        | 80 mm        |
| <a href="#">WL52920</a> | 400 mm        | 82 mm        |
| <a href="#">WL52921</a> | 400 mm        | 85 mm        |
| <a href="#">WL52922</a> | 445 mm        | 88 mm        |
| <a href="#">WL52923</a> | 445 mm        | 90 mm        |
| <a href="#">WL52924</a> | 445 mm        | 94 mm        |
| <a href="#">WL52925</a> | 445 mm        | 95 mm        |

Non-sparking tools are used in areas where there is a potential fire and explosion hazard due to flying sparks. 46 mm striking-face open-end wrench made of copper beryllium, 250 mm.

- Made of copper beryllium
- Head angle: 15°
- For use with a hammer for tightening large bolts and nuts
- DIN 133
- Non-sparking tools are used in areas where there is a potential fire and explosion hazard due to flying sparks
- Head angle of 15° for working in areas difficult to access
- Antimagnetic, extremely corrosion resistant

## PRODUCT DETAILS

|                          |                                  |
|--------------------------|----------------------------------|
| item number              | WL52903                          |
| model                    | NSB100-46                        |
| manufacturer             | BAHCO                            |
| manufacturer item number | NSB100-46                        |
| dimensions (LxWxH)       | 250 mm x 146 mm x 26 mm          |
| order unit               | piece                            |
| packaging mass           | piece                            |
| ESD safe                 | no                               |
| VDE                      | no                               |
| Type open-end spanner    | Open-end spanner                 |
| tool material            | amagnetic steel, copperberyllium |
| wrench width             | 98 mm                            |