

Bahco NSB100-65. Non-sparking 65 mm impact open-end wrench made of copper beryllium, 335 mm

Item no. WL52913

Manufacturer Bahco

Non-sparking 65 mm impact open-end wrench made of copper beryllium, 335 mm

TECHNICAL DATA

Norm DIN 133

Weight 0.1 kg



DESCRIPTION

OTHER VERSIONS

item number	length	wrench width
WL52879	485 mm	100 mm
WL52880	485 mm	105 mm
WL52881	513 mm	110 mm
WL52882	513 mm	115 mm
WL52883	530 mm	120 mm
WL52884	125 mm	17 mm
WL52885	125 mm	19 mm
WL52886	135 mm	22 mm
WL52887	150 mm	24 mm
WL52888	150 mm	25 mm
WL52889	175 mm	27 mm
WL52890	175 mm	28 mm
WL52891	190 mm	29 mm
WL52892	190 mm	30 mm

item number	length	wrench width
WL52893	190 mm	32 mm
WL52894	190 mm	33 mm
WL52895	200 mm	34 mm
WL52896	210 mm	35 mm
WL52897	210 mm	36 mm
WL52898	210 mm	37 mm
WL52899	220 mm	38 mm
WL52900	230 mm	41 mm
WL52901	230 mm	42 mm
WL52902	250 mm	45 mm
WL52903	250 mm	46 mm
WL52904	250 mm	47 mm
WL52905	275 mm	50 mm
WL52906	275 mm	52 mm
WL52907	305 mm	54 mm
WL52908	305 mm	55 mm
WL52909	305 mm	56 mm
WL52910	315 mm	58 mm
WL52911	315 mm	60 mm
WL52912	335 mm	63 mm
WL52913	335 mm	65 mm
WL52914	335 mm	67 mm
WL52915	370 mm	70 mm
WL52916	370 mm	71 mm
WL52917	375 mm	75 mm
WL52918	375 mm	77 mm
WL52919	400 mm	80 mm
WL52920	400 mm	82 mm
WL52921	400 mm	85 mm
WL52922	445 mm	88 mm
WL52923	445 mm	90 mm
WL52924	445 mm	94 mm
WL52925	445 mm	95 mm

Non-sparking tools are used in areas where there is a potential fire and explosion hazard due to flying sparks. 65 mm striking-face open-end wrench made of copper beryllium, 335 mm.

- Made of copper beryllium
- Head angle: 15°
- For use with a hammer for tightening large bolts and nuts
- DIN 133
- Non-sparking tools are used in areas where there is a potential fire and explosion hazard due to flying sparks
- Head angle of 15° for working in areas difficult to access
- Antimagnetic, extremely corrosion resistant

PRODUCT DETAILS

item number	WL52913
model	NSB100-65
manufacturer	BAHCO
manufacturer item number	NSB100-65
dimensions (LxWxH)	335 mm x 204 mm x 36 mm
order unit	piece
packaging mass	piece
ESD safe	no
VDE	no
Type open-end spanner	Open-end spanner
tool material	amagnetic steel, copperberyllium
wrench width	140 mm