

Bahco NSB220-20. 1/2" socket wrench insert made of copper beryllium, 20 mm hexagon profile, non-sparking

Item no. WL53102

Manufacturer Bahco

1/2" socket wrench insert made of copper beryllium, 20 mm hexagon profile, non-sparking

TECHNICAL DATA

Weight

0.1 kg



DESCRIPTION

OTHER VERSIONS

item number	hexagon socket
WL53088	6 mm
WL53089	7 mm
WL53090	8 mm
WL53091	9 mm
WL53092	10 mm
WL53093	11 mm
WL53094	12 mm
WL53095	13 mm
WL53096	14 mm
WL53097	15 mm
WL53098	16 mm
WL53099	17 mm
WL53100	18 mm
WL53101	19 mm

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

item number	hexagon socket
WL53102	20 mm
WL53103	21 mm
WL53104	22 mm
WL53105	23 mm
WL53106	24 mm
WL53107	25 mm
WL53108	26 mm
WL53109	27 mm
WL53110	28 mm
WL53111	29 mm
WL53112	30 mm
WL53113	32 mm

Non-sparking tools are used in areas where there is a potential fire and explosion hazard due to flying sparks. 1/2 socket wrench insert made of copper beryllium with 20 mm hexagonal profile, non-sparking.

- Made of copper beryllium
- Socket wrench inserts, standard length, 1/2" square drive
- Hexagonal profile, metric sizes
- ISO 2725/1174
- Non-sparking tools are used in areas where there is a potential fire and explosion hazard due to flying sparks
- Antimagnetic, extremely corrosion resistant

PRODUCT DETAILS

item number	WL53102
model	NSB220-20
manufacturer	BAHCO
manufacturer item number	NSB220-20
dimensions (LxWxH)	42 mm x 26 mm x 26 mm
order unit	piece
ESD safe	no
hexagon socket	20 mm
packaging mass	piece
VDE	no
tool material	amagnetic steel, copperberyllium