

Bahco NSB300-7-150. Ergo Screwdrivers made of copper beryllium for slotted screws, non-sparking, 1x7x150

Item no. WL53193

Manufacturer Bahco

ERGO Screwdrivers made of copper beryllium for slotted screws, non-sparking, 1x7x150

TECHNICAL DATA

Weight

0.1 kg



STANDARDS & COMPLIANCE

ISO 2380

DESCRIPTION

OTHER VERSIONS

item number	blade width	blade length	Blade thickness
WL53176	10 mm	200 mm	2.5 mm
WL53177	10 mm	318 mm	2.2 mm
WL53178	11 mm	250 mm	2 mm
WL53179	11 mm	300 mm	2 mm
WL53180	11 mm	350 mm	2 mm
WL53181	12 mm	400 mm	3 mm
WL53182	13 mm	450 mm	2.5 mm
WL53183	3 mm	50 mm	0.4 mm
WL53184	3 mm	75 mm	0.4 mm
WL53185	4.5 mm	95 mm	0.7 mm
WL53186	4.5 mm	60 mm	0.5 mm

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/3

item number	blade width	blade length	Blade thickness
WL53187	4 mm	75 mm	0.5 mm
WL53188	5 mm	100 mm	0.6 mm
WL53189	5 mm	75 mm	0.8 mm
WL53190	6 mm	105 mm	1 mm
WL53191	6 mm	125 mm	0.8 mm
WL53192	6 mm	160 mm	1.1 mm
WL53193	7 mm	150 mm	1 mm
WL53194	8 mm	150 mm	1.5 mm
WL53195	8 mm	200 mm	1.2 mm
WL53196	9 mm	250 mm	1.4 mm

Non-sparking tools are used in areas where there is a potential fire and explosion hazard due to flying sparks. ERGO™ Screwdrivers made of copper beryllium for slotted screws, non-sparking, 1 x 7 x 150 .

- Made of copper beryllium
- Developed according to the scientific ERGO™ process
- Screwdriver for slotted screws
- Handle made of antistatic plastic
- Manufactured according to the specifications of the ISO 2380 standard
- Non-sparking tools are used in areas where there is a potential fire and explosion hazard due to flying sparks
- Three-component handle with strong core, provides a firm grip and maximum operating comfort with optimum power transmission
- Antimagnetic, extremely corrosion resistant

PRODUCT DETAILS

item number	WL53193
model	NSB300-7-150
manufacturer	BAHCO
manufacturer item number	NSB300-7-150
dimensions (LxWxH)	270 mm x 30 mm x 30 mm
order unit	piece
handle length	122 mm
packaging mass	piece
Handle width	27 mm
type of screwdriver	normal screwdrivers
ESD safe	no
Blade thickness	1 mm

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 2/3

tool material	amagnetic steel, copperberyllium
VDE	no
blade length	150 mm
blade width	7 mm