

Bahco NSB502-5000-FB. Sledge hammer with copper beryllium head and fiberGlasss handle, spark free, 5 kg

Item no. WL53259

Manufacturer Bahco

Sledge hammer with copper beryllium head and fiberglass handle, spark free, 5 kg

TECHNICAL DATA

Weight **0.1 kg**



DESCRIPTION

OTHER VERSIONS

item number	Tool head weight & head width
WL53250	10 kg & 82 mm
WL53251	1 kg & 40 mm
WL53252	12 kg & 85 mm
WL53253	1.5 kg & 44 mm
WL53254	2 kg & 50 mm
WL53255	2.5 kg & 52 mm
WL53256	3 kg & 56 mm
WL53257	4.5 kg & 64 mm
WL53258	0.45 kg & 30 mm
WL53259	5 kg & 65 mm
WL53260	6.8 kg & 71 mm
WL53261	8 kg & 75 mm

Non-sparking tools are used in areas where there is a potential fire and explosion hazard due to

flying sparks. Sledge hammer with copper beryllium head and fibreglass handle, non-sparking, 5 kg.

- Made of copper beryllium
- Two-component fibreglass handle
- Meets the product standards according to UNE 16590
- Non-sparking tools are used in areas where there is a potential fire and explosion hazard due to flying sparks
- Without sharp edges, to avoid sparks
- Antimagnetic, extremely corrosion resistant

PRODUCT DETAILS

item number	WL53259
model	NSB502-5000-FB
manufacturer	BAHCO
manufacturer item number	NSB502-5000-FB
dimensions (LxWxH)	900 mm x 177 mm x 63 mm
order unit	piece
ESD safe	no
packaging mass	piece
Hammer type	Sledge Hammer
VDE	no
tool material	amagnetic steel, copperberyllium
head width	65 mm
Tool head weight	5 kg