

Bahco NSB504-200-FB. Engineer's hammer with copper beryllium head and fibreGlass handle, non- sparking, 200 g

Item no. WL53266

Manufacturer Bahco

Engineer's hammer with copper beryllium head and fibreglass handle, non-sparking, 200 g

TECHNICAL DATA

Norm DIN 1041

Weight 0.1 kg



STANDARDS & COMPLIANCE

DIN 1041

DESCRIPTION

OTHER VERSIONS

item number	width	Tool head weight	head width	length
WL53262	135 mm	1 kg	35 mm	355 mm
WL53263	60 mm	0.1 kg	16 mm	280 mm
WL53264	160 mm	1.5 kg	40 mm	400 mm
WL53265	170 mm	2 kg	45 mm	400 mm
WL53266	80 mm	0.2 kg	22 mm	280 mm
WL53267	100 mm	0.3 kg	23 mm	280 mm
WL53268	112 mm	0.5 kg	28 mm	310 mm
WL53269	130 mm	0.8 kg	33 mm	355 mm

Non-sparking tools are used in areas where there is a potential fire and explosion hazard due to flying sparks. Engineer's hammer with copper beryllium head and fibreglass handle, non-sparking, 200 g.

- Made of copper beryllium
- Two-component fibreglass handle
- Meets the product standards according to DIN 1041
- Non-sparking tools are used in areas where there is a potential fire and explosion hazard due to flying sparks
- Without sharp edges, to avoid sparks
- Antimagnetic, extremely corrosion resistant

PRODUCT DETAILS

item number	WL53266
model	NSB504-200-FB
manufacturer	BAHCO
manufacturer item number	NSB504-200-FB
dimensions (LxWxH)	280 mm x 80 mm x 20 mm
order unit	piece
ESD safe	no
packaging mass	piece
Hammer type	engineer's hammer
VDE	no
tool material	amagnetic steel, copperberyllium
head width	22 mm
Tool head weight	0.2 kg