

Bahco BE-8915SL. Ergo-Torx-Screwdriver with three-component handle, VDE insulated, SLIM, T15x100 mm

Item no. **WL53517**

Manufacturer **Bahco**

ERGO-TORX-Screwdriver with three-component handle, VDE insulated, SLIM, T15x100 mm

TECHNICAL DATA

Weight

0.1 kg



STANDARDS & COMPLIANCE

ISO 2380 IEC 60900 DIN 5264

DESCRIPTION

OTHER VERSIONS

item number	type of screw	blade length
WL53514	TX10	100 mm
WL53517	TX15	100 mm
WL53520	TX20	100 mm
WL53523	TX25	125 mm
WL53526	TX30	150 mm

- Screwdriver developed in the course of the ERGO™ process
- VDE-insulated ERGO™ Screwdriver with slim blades (reduced blade diameter) for TORX® screws
- Phosphated tip for greater precision ensures a precise fit and prevents flaking
- For work on live equipment up to 1000 V. Insulation sprayed directly onto the blade
- 3-component handle for maximum ease of use, soft material with rigid surface provides comfortable grip and better power transmission
- The correct blade can be easily identified by the colour marking and the symbol on the end of the

handle

- Flat side parts prevent the screwdriver from rolling away
- Integrated suspension opening
- High-quality insulation layer sprayed directly onto the blade
- Blades are 30% slimmer than conventional insulated blades for better accessibility
- Standards: ISO 2380/DIN 5264
- Individually tested and manufactured according to IEC 60900, tested in a water bath at 10,000 V

PRODUCT DETAILS

item number	WL53517
model	BE 8915SL
manufacturer	BAHCO
manufacturer item number	BE-8915SL
dimensions (LxWxH)	222 mm x 20 mm x 65 mm
order unit	piece
handle length	122 mm
VDE	yes
ESD safe	no
type of screw	TX15
packaging mass	piece
Handle width	20 mm
type of screwdriver	normal screwdrivers
tool length	222 mm
handle diameter	20 mm
blade length	100 mm