

Knipex 49 41 A21. Precision circlip pliers for outer rings on shafts, gray atramentized, 165 mm

Item no. WL61600

Manufacturer Knipex

Precision circlip pliers for outer rings on shafts, gray atramentized, 165 mm

TECHNICAL DATA

Colour	Grey
Weight	0.1 kg



STANDARDS & COMPLIANCE

DIN 5254 DIN 471

DESCRIPTION

OTHER VERSIONS

item number	tip diameter	tool length
WL61598	0.9 mm	130 mm
WL61599	1.3 mm	130 mm
WL61600	1.8 mm	165 mm
WL61601	2.3 mm	210 mm

Precision circlip pliers with high load capacity for continuous use: up to 10 times longer service life compared to screwed-on tips. With inserted tips for safe working. Highly durable in continuous use, up to 10 times longer service life. Precise, smooth-running screw joint. Forged. Large contact surfaces on the tips: no torsion of the rings, easy assembly. Slim pliers head for optimum access to the workpiece. Opening spring located in the joint, protected and captive. Handles covered with non-slip plastic. DIN 5254 B; 90° angled tips. with expansion stop for standard-compliant assembly in accordance with DIN 471. the adjustable stop screw prevents overstretching of the rings. - capacity for shaft diameter: Ø 19 - 60mm - shape: 4 - tips (diameter): 1,8mm

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

- Highly durable in continuous use, up to 10 times longer service life
- Precise, smooth-running screw joint
- Forged
- Large contact surfaces at the tips: no torsion of the rings, easy assembly
- Slim pliers head for optimum access to the workpiece
- Opening spring located in the joint, protected and captive
- Handles coated with non-slip plastic

PRODUCT DETAILS

item number	WL61600
model	49 41 A21
manufacturer	KNIPEX
manufacturer item number	49 41 A21
dimensions (LxWxH)	175 mm x 36 mm x 13 mm
dimensions with packaging (LxWxH)	189 mm x 72 mm x 48 mm
Packaging volume	0.637 dm ³
order unit	piece
type of packaging	single pack
standards	DIN 5254 B
RoHS conform	no
surface	grey atramentised
VDE	no
tip diameter	1.8 mm
jaw angle	Jaws, angled, 90
ESD safe	no
tool length	165 mm
type of handle	Covered with non-slip plastic
type of pliers	snap ring pliers