

Knipex 70 06 160 T. Side cutters, chrome-plated, insulated, fixing eye, 160 mm

Item no. WL61646

Manufacturer Knipex

Side cutters, chrome-plated, insulated, fixing eye, 160 mm

TECHNICAL DATA

Weight 0.1 kg



STANDARDS & COMPLIANCE

EN 60900 DIN ISO 5749 IEC 60900

DESCRIPTION

OTHER VERSIONS

item number	tether attachment point	tool length
WL23697	nein	160 mm
WL23702	nein	140 mm
WL61645	nein	125 mm
WL61646	ja	160 mm
WL61647	ja	180 mm
WL61648	nein	180 mm

The indispensable side cutter for versatile use. High-quality material and precise workmanship for a long service life. Precision cutting edges for soft and hard wire. Clean cut on thin Cu-wires, also at the cutting tips. Cutting edges additionally induction hardened, cutting edge hardness approx. 62 HRC. Slim head shape for use in hard-to-reach work areas. With extended cutting edge. Pliers with integrated insulated fastening eye for attaching a fall protection device. - Cutting values medium-

hard wire (diameter): Ø 3.0mm - Cutting values hard wire (diameter): Ø 2mm - Cutting values soft wire (diameter): Ø 4.0mm - Fall protection: Yes - VDE-tested: Yes

- The indispensable side cutter for versatile use
- High-quality material and precise workmanship for a long service life
- Precision cutting edges for soft and hard wire
- Clean cut on thin Cu-wires, also at the cutting tips
- Cutting edges additionally induction hardened, cutting edge hardness approx. 62 HRC
- Slim head shape for use in hard-to-reach working areas

PRODUCT DETAILS

item number	WL61646
model	70 06 160 T
manufacturer	KNIPEX
manufacturer item number	70 06 160 T
dimensions (LxWxH)	169 mm x 54 mm x 28 mm
dimensions with packaging (LxWxH)	177 mm x 61 mm x 30 mm
Packaging volume	0.326 dm ³
order unit	piece
type of packaging	single pack
standards	DIN EN 60900, DIN ISO 5749 IEC 60900
RoHS conform	no
surface	chrome-plated
VDE	yes
tether attachment point	ja
ESD safe	no
tool length	160 mm
description head	Chrome-plated
type of handle	VDE, Tethered Tools insulated with multi-component sheaths, VDE-tested; with integrated insulated fastening eyelet for attaching a fall protection device
cutting value wire diameter hard	2 mm
cutting value wire diameter medium	3 mm
cutting value wire diameter soft	4 mm