

Knipex 71 32 200 T. CoBolt compact bolt cutter, black atramentized, fastening eyelet, 200 mm

Item no. WL61661

Manufacturer Knipex

CoBolt compact bolt cutter, black atramentized, fastening eyelet, 200 mm

TECHNICAL DATA

Colour **Black**

Weight **0.1 kg**



DESCRIPTION

OTHER VERSIONS

item number	tether attachment point
WL61661	ja
WL61662	nein

KNIPLEX CoBolt® With precision cutting edges for soft, hard and piano wire. Cuts components such as bolts, nails, rivets etc. up to Ø 5.2 mm. Particularly high cutting performance with less effort due to highly efficient joint design. With recess to facilitate cutting of thicker wires. Cutting edges additionally induction hardened, cutting edge hardness approx. 64 HRC. Opening spring and locking mechanism integrated in the handle sleeves for comfortable working and safe transport. with slim multi-component sleeves without collar for better handling and easier transport. with gripping surface under the joint for gripping and pulling wires from Ø 1.0 mm. Pliers with fastening eye for attaching a fall protection device. the recess in the cutting edge makes it easier to cut thicker wires, e.g. in suspended ceiling constructions. - shape: 3 - cutting values soft wire (diameter): Ø 6mm - cutting values medium hard wire (diameter): Ø 5,2mm - cutting values hard wire (diameter): Ø 4,0mm - cutting values piano wire (diameter): Ø 3,6mm - fall protection: yes

- With precision cutting edges for soft, hard and piano wire
- Cuts components such as bolts, nails, rivets etc. up to Ø 5.2 mm

- Particularly high cutting performance with less effort due to highly efficient joint design
- With recess to facilitate cutting of thicker wires
- Cutting edges additionally induction hardened, cutting edge hardness approx. 64 HRC

PRODUCT DETAILS

item number	WL61661
model	71 32 200 T
manufacturer	KNIPEX
manufacturer item number	71 32 200 T
dimensions (LxWxH)	200 mm x 55 mm x 23 mm
dimensions with packaging (LxWxH)	211 mm x 66 mm x 30 mm
Packaging volume	0.41 dm ³
order unit	piece
type of packaging	single pack
product series	CoBolt®
RoHS conform	no
surface	black atramentised
VDE	no
Sheathing handle	with multi-component sleeves
ESD safe	no
tether attachment point	ja
tool length	200 mm
type of handle	Tethered Tools with slim multi-component sheaths, with integrated fastening eyelet for attaching a fall protection device
cutting value wire diameter hard	4 mm
cutting value wire diameter medium	5.2 mm
cutting value wire diameter soft	6 mm
type of pliers	bolt cutters