

Knipex 74 05 250. Heavy-duty side cutter, chrome-plated, 250 mm

Item no. WL61697

Manufacturer Knipex

Heavy-duty side cutter, chrome-plated, 250 mm

TECHNICAL DATA

Weight

0.1 kg



STANDARDS & COMPLIANCE

ISO 5749

DESCRIPTION

OTHER VERSIONS

item number	tether attachment point	tool length
WL61693	nein	140 mm
WL61694	nein	160 mm
WL61695	nein	180 mm
WL61696	nein	200 mm
WL61697	nein	250 mm

For the toughest, continuous use. High cutting performance with low effort due to optimum coordination of cutting edge angle and transmission ratio. Precision cutting edges additionally induction hardened, (cutting edge hardness approx. 64 HRC) for all wire types including piano wire. The 250 mm long side cutter is suitable for Cu conductors up to 16 mm² and Al conductors up to 35 mm². - shape: 0 - cutting values medium hard wire (diameter): Ø 4,6mm - cutting values hard wire (diameter): Ø 3,5mm - cutting values piano wire (diameter): Ø 3,0mm

- For the hardest, permanent use
- High cutting performance with low effort due to optimum coordination of cutting edge angle and transmission ratio
- Precision cutting edges additionally induction hardened, (cutting edge hardness approx. 64 HRC) for all wire types including piano wire

PRODUCT DETAILS

item number	WL61697
model	74 05 250
manufacturer	KNIPEX
manufacturer item number	74 05 250
dimensions (LxWxH)	250 mm x 54 mm x 24 mm
dimensions with packaging (LxWxH)	324 mm x 124 mm x 51 mm
Packaging volume	2.049 dm ³
order unit	piece
type of packaging	single pack
standards	DIN ISO 5749
RoHS conform	no
surface	chrome-plated
ESD safe	no
VDE	no
Sheathing handle	with multi-component sleeves
tether attachment point	nein
insulated	no
tool length	250 mm
description head	chrome-plated
type of handle	with multi-component sleeves
cutting value wire diameter hard	3.5 mm
cutting value wire diameter medium	4.6 mm