

Knipex 74 06 250 T. Heavy-duty side cutter, chrome-plated, insulated, fastening eyelet, 250 mm

Item no. WL61701 **Manufacturer** Knipex

Manufacturer no. 74 06 250 T

Heavy-duty side cutter, chrome-plated, insulated, fastening eyelet, 250 mm

TECHNICAL DATA

Article authenticity	Original product
Condition of article	New
Weight	0.1 kg



STANDARDS & COMPLIANCE

EN 60900 DIN ISO 5749 IEC 60900

DESCRIPTION

Other versions

item number	tether attachment	point	tool length
WL13357	nein		200 mm
WL61698	nein		160 mm
WL61699	nein		180 mm
WL61700	ja		200 mm
WL61701	ja		250 mm
WL61702	nein		250 mm

For the toughest, permanent use. High cutting performance with low effort due to optimum coordination of cutting edge angle and transmission ratio. Precision cutting edges additionally induction hardened, (cutting edge hardness approx. 64 HRC) for all wire types including piano wire. Pliers with integrated insulated fastening eye for attaching a fall protection device. - Shape: 0 - Cutting values medium-hard wire (diameter): Ø 4.6mm - Cutting values hard wire (diameter): Ø 3.5mm - Cutting values piano wire (diameter): Ø 3.0mm - Fall protection: Yes - VDE-tested: Yes

- For the hardest, permanent use

- High cutting performance with low effort due to optimum coordination of cutting edge angle and transmission ratio
- Precision cutting edges additionally induction hardened, (cutting edge hardness approx. 64 HRC) for all wire types including piano wire

Product details

item number	WL61701
model	74 06 250 T
manufacturer	KNIPEX
manufacturer item number	74 06 250 T
dimensions (LxWxH)	254 mm x 61 mm x 29 mm
dimensions with packaging (LxWxH)	262 mm x 71 mm x 30 mm
Packaging volume	0.546 dm ³
order unit	piece
type of packaging	single pack
standards	DIN EN 60900, DIN ISO 5749 IEC 60900
RoHS conform	no
surface	chrome-plated
ESD safe	no
VDE	yes
Sheathing handle	with multi-component sleeves
tether attachment point	ja
insulated	yes
tool length	250 mm
description head	chrome-plated
type of handle	VDE, Tethered Tools insulated with multi-component sleeves, VDE-tested; with integrated insulated fastening eye for attaching a fall protection device
cutting value wire diameter hard	3.5 mm
cutting value wire diameter medium	4.6 mm