

Knipex 74 06 250. Heavy-duty side cutter, chrome-plated, insulated, 250 mm

Item no. WL61702

Manufacturer Knipex

Heavy-duty side cutter, chrome-plated, insulated, 250 mm

TECHNICAL DATA

Weight

0.1 kg



STANDARDS & COMPLIANCE

EN 60900 DIN ISO 5749 IEC 60900

DESCRIPTION

OTHER VERSIONS

item number	tether attachment point	tool length
WL13357	nein	200 mm
WL61698	nein	160 mm
WL61699	nein	180 mm
WL61700	ja	200 mm
WL61701	ja	250 mm
WL61702	nein	250 mm

For the toughest, permanent use. High cutting performance with low effort due to optimum coordination of cutting edge angle and transmission ratio. Precision cutting edges additionally induction hardened, (cutting edge hardness approx. 64 HRC) for all wire types including piano wire. The 250 mm long side cutter is suitable for Cu conductors up to 16 mm² and Al conductors up to 35 mm². - Shape: 0 - Cutting values medium-hard wire (diameter): Ø 4.6mm - Cutting values hard wire

(diameter): Ø 3.5mm - Cutting values piano wire (diameter): Ø 3.0mm - VDE-tested: Yes

- For the toughest, permanent use
- High cutting performance with low effort due to optimum coordination of cutting edge angle and transmission ratio
- Precision cutting edges additionally induction hardened, (cutting edge hardness approx. 64 HRC) for all wire types including piano wire

PRODUCT DETAILS

item number	WL61702
model	74 06 250
manufacturer	KNIPEX
manufacturer item number	74 06 250
dimensions (LxWxH)	255 mm x 63 mm x 22 mm
dimensions with packaging (LxWxH)	262 mm x 71 mm x 30 mm
Packaging volume	0.546 dm ³
order unit	piece
type of packaging	single pack
standards	DIN EN 60900, DIN ISO 5749 IEC 60900
RoHS conform	no
surface	chrome-plated
ESD safe	no
VDE	yes
Sheathing handle	with multi-component sleeves
tether attachment point	nein
insulated	yes
tool length	250 mm
description head	chrome-plated
type of handle	VDE insulated with multi-component sleeves, VDE-tested
cutting value wire diameter hard	3.5 mm
cutting value wire diameter medium	4.6 mm