

Knipex 74 07 250. Heavy-duty side cutter, chrome-plated, dip-insulated, 250 mm

Item no. WL61704

Manufacturer Knipex

Heavy-duty side cutter, chrome-plated, dip-insulated, 250 mm

TECHNICAL DATA

Weight

0.1 kg



STANDARDS & COMPLIANCE

EN 60900 DIN ISO 5749 IEC 60900

DESCRIPTION

OTHER VERSIONS

item number	tool length
WL61703	200 mm
WL61704	250 mm

For the toughest, permanent use. High cutting performance with low effort due to optimum coordination of cutting edge angle and transmission ratio. Precision cutting edges additionally induction hardened, (cutting edge hardness approx. 64 HRC) for all wire types including piano wire. The 250 mm long side cutter is suitable for Cu conductors up to 16 mm² and Al conductors up to 35 mm². - Shape: 0 - Cutting values medium-hard wire (diameter): Ø 4.6mm - Cutting values hard wire (diameter): Ø 3.5mm - Cutting values piano wire (diameter): Ø 3.0mm - VDE-tested: Yes

- For the toughest, permanent use
- High cutting performance with low effort due to optimum coordination of cutting edge angle and transmission ratio
- Precision cutting edges additionally induction hardened, (cutting edge hardness approx. 64 HRC)

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

for all wire types including piano wire

PRODUCT DETAILS

item number	WL61704
model	74 07 250
manufacturer	KNIPEX
manufacturer item number	74 07 250
dimensions (LxWxH)	260 mm x 75 mm x 36 mm
dimensions with packaging (LxWxH)	272 mm x 81 mm x 40 mm
Packaging volume	0.864 dm ³
order unit	piece
type of packaging	single pack
standards	DIN EN 60900, DIN ISO 5749 IEC 60900
RoHS conform	no
surface	chrome-plated
VDE	yes
ESD safe	no
tool length	250 mm
description head	chrome-plated
type of handle	VDE dip-insulated, VDE-tested
cutting value wire diameter hard	3.5 mm
cutting value wire diameter medium	4.6 mm