

Knipex 74 22 250. Power side cutter, black atramentized, 250 mm

Item no. WL61712

Manufacturer Knipex

Power side cutter, black atramentized, 250 mm

TECHNICAL DATA

 Colour **Black**

 Weight **0.1 kg**


STANDARDS & COMPLIANCE

ISO 5749

DESCRIPTION

OTHER VERSIONS

item number	tether attachment point	tool length
WL61709	ja	200 mm
WL61710	nein	200 mm
WL61711	ja	250 mm
WL61712	nein	250 mm

For the toughest, permanent use. High cutting performance with low effort due to optimum coordination of cutting edge angle and transmission ratio. Precision cutting edges additionally induction hardened, (cutting edge hardness approx. 64 HRC) for all wire types including piano wire. The 250 mm long side cutter is suitable for Cu conductors up to 16 mm² and Al conductors up to 35 mm². 12° angled head offers free space for gripping. - Shape: 2 - Cutting values medium-hard wire (diameter): Ø 4.6mm - Cutting values hard wire (diameter): Ø 3.5mm - Cutting values piano wire (diameter): Ø 3.0mm

- For the hardest, permanent use
- High cutting performance with low effort due to optimum coordination of cutting edge angle and transmission ratio
- Precision cutting edges additionally induction hardened, (cutting edge hardness approx. 64 HRC) for all wire types including piano wire

PRODUCT DETAILS

item number	WL61712
model	74 22 250
manufacturer	KNIPEX
manufacturer item number	74 22 250
dimensions (LxWxH)	250 mm x 51 mm x 22 mm
dimensions with packaging (LxWxH)	324 mm x 124 mm x 51 mm
Packaging volume	2.066 dm ³
order unit	piece
type of packaging	single pack
standards	DIN ISO 5749
RoHS conform	no
surface	black atramentised
tether attachment point	nein
VDE	no
jaw angle	Jaws, angled, 12
ESD safe	no
tool length	250 mm
description head	polished
type of handle	with multi-component sheaths
cutting value wire diameter hard	3.5 mm
cutting value wire diameter medium	4.6 mm