

Knipex 79 02 125 S1. Precision electronics side cutter, burnished, 125 mm

Item no. WL61730

Manufacturer Knipex

Precision electronics side cutter, burnished, 125 mm

TECHNICAL DATA

Weight

0.1 kg



STANDARDS & COMPLIANCE

ISO 9654

DESCRIPTION

Precision pliers for the finest cutting work, e.g. in electronics and precision mechanics. Very precisely ground, sharp cutting edges with very small facets for exact cuts on sensitive electronic components; also available without facet for flush cutting. Cutting edges additionally induction hardened, cutting edge hardness approx. 64 HRC. Approx. 20 % less weight than conventional electronic pliers. Bolted joint with particularly carefully manufactured joint surfaces for uniform, low-friction movement in the entire opening range. Smooth-running double spring for smooth and even opening. Ergonomically optimised multi-component sleeves. round head. all edges on the head rounded - reduces the risk of insulation damage when correcting wiring harnesses. - Shape: 0 - cutting values medium hard wire (diameter): Ø 1,3mm - cutting values hard wire (diameter): Ø 0,7mm - cutting values soft wire (diameter): Ø 0,2 - 1,7mm - jaw length (B): 10mm - jaw thickness (at joint) (D): 6,5mm - head width (A): 11mm

- Precision pliers for finest cutting work, e.g. in electronics and precision mechanics
- Very precisely ground, sharp cutting edges with very small facets for exact cuts on sensitive electronic components
- Also without facet for flush cutting

- Cutting edges additionally induction hardened, cutting edge hardness approx. 64 HRC
- Approx. 20 % less weight than conventional electronic pliers
- Bolted joint with particularly carefully manufactured joint surfaces for uniform, low-friction movement in the entire opening range
- Smooth-running double spring for smooth and even opening
- Ergonomically optimised multi-component handles

PRODUCT DETAILS

item number	WL61730
model	79 02 125 S1
manufacturer	KNIPEX
manufacturer item number	79 02 125 S1
dimensions (LxWxH)	130 mm x 59 mm x 19 mm
dimensions with packaging (LxWxH)	189 mm x 72 mm x 48 mm
Packaging volume	0.637 dm ³
order unit	piece
type of packaging	single pack
standards	DIN ISO 9654
RoHS conform	no
surface	burnished
ESD safe	no
VDE	no
jaw thickness	6.5 mm
description head	polished
type of handle	with multi-component sleeves
length of jaws	10 mm
cutting value wire diameter hard	0.7 mm
cutting value wire diameter medium	1.3 mm
cutting value wire diameter soft	1.7 mm
type of pliers	electronic pliers